



AGRICULTURAL FLOTATION TYRES

DELCORA[®]

FLX-1

FLG-1



HBI

TYRES & WHEELS








DELBCORA®

FLX-1

FLG-1



SPECIFICATIONS

 Tyre size	 Pattern	Type TT / TL	LS	 Overall diameter (mm)	 Section width (mm)	 Rim	 Tread depth (mm)	IP (BAR)	 Max. load capacity 40km/h
560/45R22.5	FLX-1	TL	152D	1076	543	16.00x22.5	18	4	4830
560/60R22.5	FLX-1	TL	165D	1244	543	16.00x22.5	18	5	6975
580/65R22.5	FLX-1	TL	166D	1326	585	16.00x22.5	20	4	7175
600/50R22.5	FLG-1	TL	163D	1172	611	20.00x22.5	25	4	6600
600/55R26.5	FLX-1	TL	165D	1333	611	20.00x26.5	20	4	6975
650/55R26.5	FLX-1	TL	169D	1389	645	20.00x26.5	24	4	7850
710/50R26.5	FLX-1	TL	170D	1383	727	24.00x26.5	24	4	8125
750/60R30.5	FLX-1	TL	170D	1691	785	24.00x30.5	26	4	11170

- Steel belted
- Large contact area
- Low contact pressure
- Self cleaning
- Stable driving behaviour
- Perfect load distribution
- Easy rolling

AGRICULTURAL FLOTATION TYRES

A product of

HBI
TYRES & WHEELS

Head office

Hollandse Bandenmarkt Internationaal BV

Stevinweg 25 • 4691 SM Tholen • The Netherlands
T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com

www.hbi-tyres.com