

TYRES FOR AGRICULTURAL MACHINERY



BANDENMARKT[®]
HEAVY DUTY TYRES

HBI
TYRES & WHEELS

Head office
Hollandse Bandenmarkt Internationaal BV
Stevinweg 25 • 4691 SM Tholen • The Netherlands
T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com

HBI
TYRES & WHEELS

TYRES FOR AGRICULTURAL MACHINERY



SPECIFICATIONS

PATTERNS



Inch	Tyre size	Pattern	PR/LI	TT/TL	Rim size	Tread depth	Overall diameter (mm)	Section width (mm)	Max. load capacity 40km/h	IP (bar)
14.5	30x11.5-14.5 (12.5/60-15)	Flotagrip-HD	150A8	TT	10.00-14.5	10	750	275	3350	8.0
17.5	215/75R17.5	HT+	135/133J	TL	6.00x17.5	10	780	220	2500	8.5
	235/75R17.5	HT+ Protector	135/133J	TL	6.00x17.5	10	780	220	2500	8.5
19	14.5/80-19	HT+	143/141J	TL	6.75x17.5	12	811	242	3130/2950	8.6
	435/50R19.5	HT+ Protector	143/141J	TL	6.75x17.5	12	811	242	3130/2950	8.6
19.5	445/45R19.5	Flotagrip-4	24PR	TT	11.00-19A	15	980	355	5500	6.5
	445/45R19.5	HT	160F	TL	14.00x19.5	12	931	438	5400	9.0
20	18.00-20	Kargo-Radial	160F	TL	14.00x19.5	17	940	445	5400	9.0
	18R20	RL-Silex	26PR	TT	13.00-20	23	1380	480	6500	6.0
20	1300x530-508 (B-20)	Flotagrip-Radial	172A8/169D	TL	14x20.5	18	1130	430	6300	6.0
	50x21.0-20	FR+	172A8/169D	TL	14x20.5	25	1146	430	6300	6.0
22.5	295/60R22.5	Kargo-Radial	172A8/169D	TL	14x20.5	17	1122	435	6300	6.0
	305/55R22.5	BN3	173A8	TT	15.00-20A	26	1230	540	7600	6.0
22.5	315/60R22.5	Flotagrip	28pr	TL	15.00-20A	18	1230	535	6500	6.0
	315/70R22.5	NZA	150/147K	TL	9.00x22.5	14	940	292	3850	9.0
22.5	315/80R22.5	Kargo-Radial	156/154A8	TL	9.00x22.5	13	930	300	4000	7.0
	315/80R22.5	Rib	156/154A8	TL	9.00x22.5	11	930	300	4000	7.0
22.5	315/80R22.5	GSP+	156/154A8	TL	9.00x22.5	9	950	313	4000	9.0
	315/80R22.5	GSP+	158/156A8	TL	9.00x22.5	9	1014	312	4250	9.0
22.5	355/50R22.5	NZA	161A8	TL	9.00x22.5	14	1085	317	4620	8.5
	385/55R22.5	NGRML	159A8	TL	11.75x22.5	12	928	361	4300	9.0
22.5	385/55R22.5	HT+	160F	TL	11.75x22.5	11	996	386	5400	9.0
	385/55R22.5	Kargo-Radial	160F	TL	11.75x22.5	17	996	386	5400	9.0
22.5	385/55R22.5	Y1	160F	TL	11.75x22.5	12	996	386	5400	9.0
	385/65R22.5	GSP+	160F	TL	11.75x22.5	11	1080	385	5400	9.0
22.5	400/70R22.5	Y1	160F	TL	11.75x22.5	12	1080	385	5400	9.0
	400R22.5	ZZ-Miler	160F	TL	11.75x22.5	15	1080	385	5400	9.0
22.5	400R22.5	ZA	160F	TL	11.75x22.5	12	1080	385	5400	9.0
	425/65R22.5	Grader	18PR	TL	11.75x22.5	25	1100	400	5400	9.0
22.5	425/65R22.5	Flotagrip+	160F	TL	11.75x22.5	20	1080	390	5400	9.0
	455/40R22.5	Kargo-Radial	160F	TL	11.75x22.5	17	1080	390	5400	9.0
22.5	455/40R22.5	ZZ	168A8	TL	14.00x22.5	12	1120	425	5600	8.0
	18R22.5	HT+	163D	TL	14.00x22.5	15	940	430	5400	9.0
22.5	500/45R22.5	ZA	170A8	TL	14.00x22.5	12	1160	455	6000	8.0
	500/45R22.5	Flotagrip	170A8	TL	14.00x22.5	18	1160	455	6000	8.0
22.5	500/45R22.5	Kargo-Radial	170A8	TL	14.00x22.5	16	1160	455	6000	8.0
	500/45R22.5	Y1	170A8	TL	14.00x22.5	18	1160	455	6000	8.0
22.5	500/45R22.5	BMT09	163D	TL	16.00x22.5	20	1030	490	5200	8.0
	19.5R22.5	GSP+	163D	TL	16.00x22.5	16	1020	490	5200	8.0
22.5	560/60R22.5	FR+	173A8/170D	TL	W14x22.5	25	1235	500	6500	6.0
	560/60R22.5	GSP+	173A8/170D	TL	W14x22.5	20	1220	500	6500	6.0
22.5	560/60R22.5	HT+	173A8/170D	TL	W14x22.5	22	1239	500	6500	6.0
	560/60R22.5	Kargo-Radial	173A8/170D	TL	W14x22.5	20	1220	500	6500	6.0
22.5	560/60R22.5	RL-Silex	173A8/170D	TL	W14x22.5	22	1230	500	6500	6.0
	20.5R22.5	Kargo-Radial	173A8/170D	TL	W16x22.5	17	1230	530	6500	6.0
22.5	560/60R22.5	RL-Silex	173A8/170D	TL	W16x22.5	30	1250	530	6500	6.0
	560/60R22.5	FR+	173A8/170D	TL	W16x22.5	25	1284	560	6500	6.0
22.5	560/60R22.5	GSP+	173A8/170D	TL	W16x22.5	22	1255	560	6500	6.0
	23	600/65R23	BMT	184A8/180D	TL	19.00x23	31	1385	570	8000
23	600/65R23	Flotagrip-Radial	184A8/180D	TL	19.00x23	17	1370	570	8000	6.0
	600/65R23	FR+	184A8/180D	TL	19.00x23	25	1365	570	8000	6.0
23	600/65R23	Kargo-Radial	184A8/180D	TL	19.00x23	17	1320	570	8000	6.0
	600/65R23	TP-Radial	184A8/180D	TL	19.00x23	31	1385	570	8000	6.0



- Up to 70% reduction of oil consumption
- Up to 80% reduction of chemical consumption
- Less consumption of other raw materials
- Less waste; retreading is truly recycling

Other sizes on request. Other compounds on request.



Head office
Hollandse Bandenmarkt Internationaal BV

Stevinweg 25 • 4691 SM Tholen • The Netherlands
T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com



www.hbi-tyres.com