

ATV TIRES

ATV TIRES



W 207



W 207 is BKT's all-terrain tire suitable for ATVs. Its design provides the best traction in any condition while the "E" marking allows the use on public roads. This tire features an excellent puncture resistance over challenging terrains.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8"										
AT 22 X 11 - 8	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
9"										
AT 22 X 11 - 9	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	300	632	-	-	STD	6	TL	-
AT 25 X 13 - 9	10.5 AT	10.0 AT	330	635	-	-	STD	6	TL	-
10"										
AT 22 X 7 - 10	5.5 AT	6.0 AT	178	559	-	-	STD	6	TL	-
AT 22 X 8 - 10	6.5 AT	6.0 AT	203	559	-	-	STD	6	TL	-
AT 22 X 11 - 10	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
AT 23 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	249	587	-	-	STD	6	TL	-
AT 23 X 7 - 10	5.5 AT	6.0 AT	177	584	-	-	STD	6	TL	-
AT 23 X 8 - 10	6.5 AT	6.0 AT	203	589	-	-	STD	6	TL	-
AT 24 X 11 - 10	9.0 AT	8.5 AT	279	610	-	-	STD	6	TL	-
AT 25 X 11 - 10	9.0 AT	8.5 AT	285	640	-	-	STD	6	TL	-
AT 25 X 12 - 10	9.5 AT	9.0 AT; 10.0 AT	297	640	-	-	STD	6	TL	-

STD: Standard



W 207



W 207 is BKT's all-terrain tire suitable for ATVs. Its design provides the best traction in any condition while the "E" marking allows the use on public roads. This tire features an excellent puncture resistance over challenging terrains.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
11" AT 23 X 8 - 11	6.5 AT	6.0 AT	203	584	-	-	STD	6	TL	-
AT 24 X 8 - 11	6.5 AT	6.0 AT	203	612	-	-	STD	6	TL	-
AT 24 X 9 - 11	7.0 AT	7.5 AT	226	610	-	-	STD	6	TL	-

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index



W 207



W 207 is BKT's all-terrain tire suitable for ATVs. Its design provides the best traction in any condition while the "E" marking allows the use on public roads. This tire features an excellent puncture resistance over challenging terrains.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
11"										
AT 24 X 10 - 11	8.0 AT	7.5 AT; 8.5 AT	249	612	-	-	STD	6	TL	-
AT 25 X 8 - 11	6.5 AT	6.0 AT	203	638	-	-	STD	6	TL	-
AT 25 X 10 - 11	8.0 AT	7.5 AT; 8.5 AT	249	638	-	-	STD	6	TL	-
12"										
AT 24 X 8 - 12	6.5 AT	6.0 AT	198	615	-	-	STD	6	TL	-
AT 25 X 8 - 12	6.5 AT	6.0 AT	198	638	-	-	STD	6	TL	-
AT 25 X 8 - 12	6.5 AT	6.0 AT	198	638	-	-	SPL	6	TL	-
AT 25 X 10 - 12	8.0 AT	6.5 AT; 7.5 AT; 8.5 AT	249	638	-	-	STD	6	TL	-
AT 25 X 11 - 12	9.0 AT	8.5 AT	284	638	-	-	STD	6	TL	-
AT 26 X 8 - 12	6.50 AT	6.00 AT	204	660	-	-	STD	6	TL	-
AT 26 X 10 - 12	8.0 AT	7.5 AT; 8.5 AT	241	658	-	-	STD	6	TL	-
AT 26 X 12 - 12	9.5 AT	8.0 AT; 8.5 AT; 9.0 AT	299	658	-	-	STD	6	TL	-
AT 27 X 10 - 12	8.0 AT	7.5 AT; 8.5 AT	241	683	-	-	STD	6	TL	-
AT 27 X 12 - 12	9.5 AT	8.5 AT; 9.0 AT	299	683	-	-	STD	6	TL	-
AT 28 X 10 - 12	8.0 AT	7.5 AT; 8.5 AT	241	706	-	-	STD	6	TL	-
AT 28 X 12 - 12	9.5 AT	8.5 AT; 9.0 AT	299	706	-	-	STD	6	TL	-

STD: Standard



AT 112

AT 112 is an all-terrain tire for ATVs. It is particularly suitable for loose surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8"										
AT 20 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	240	510	-	-	STD	4	TL	-
10"										
AT 20 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	240	510	-	-	STD	4	TL	-
12"										
AT 23 X 10 - 12	9.0 AT	8.5 AT	240	585	-	-	STD	4	TL	-

STD: Standard




Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index



AT 108



AT 108 is an all-terrain tire suitable for ATVs. Its tread design provides excellent traction on loose surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec. 	Alt.								
8"										
AT 20 X 7 - 8	5.5 AT	6.0 AT	170	508	-	-	STD	4	TL	-
AT 22 X 11 - 8	9.0 AT	8.5 AT	277	560	-	-	STD	4	TL	-
9"										
AT 22 X 10 - 9	8.0 AT	7.5 AT; 8.5 AT	254	559	-	-	STD	4	TL	-
AT 22 X 11 - 9	9.0 AT	8.5 AT	275	557	-	-	STD	4	TL	-
AT 22 X 11 - 9	9.0 AT	8.5 AT	275	557	-	-	STD	6	TL	-
AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	292	640	-	-	STD	4	TL	-
AT 25 X 13 - 9	10.5 AT	10.0 AT	320	635	-	-	STD	4	TL	-
AT 25 X 13 - 9	10.5 AT	10.0 AT	320	635	-	-	STD	6	TL	-
10"										
AT 20 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	250	514	-	-	STD	4	TL	-
AT 22 X 8 - 10	6.5 AT	6.0 AT	206	557	-	-	STD	4	TL	-
AT 22 X 8 - 10	6.5 AT	6.0 AT	206	557	-	-	STD	6	TL	-
AT 22 X 11 - 10	9.0 AT	8.5 AT	270	564	-	-	STD	4	TL	-
AT 22 X 11 - 10	9.0 AT	8.5 AT	270	564	-	-	STD	6	TL	-
AT 23 X 8 - 10	6.5 AT	6.0 AT	210	594	-	-	STD	4	TL	-
AT 23 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	259	594	-	-	STD	4	TL	-

STD: Standard



AT 108



AT 108 is an all-terrain tire suitable for ATVs. Its tread design provides excellent traction on loose surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
10"										
AT 24 X 11 - 10	9.0 AT	8.5 AT	284	608	-	-	STD	4	TL	-
24 X 11 - 10	9.0	-	284	608	-	-	STD	6	TL	-
AT 25 X 12 - 10	9.5 AT	9.0 AT; 10.0 AT	298	630	-	-	STD	4	TL	-
AT 25 X 12 - 10	9.5 AT	9.0 AT; 10.0 AT	298	630	-	-	STD	6	TL	-
11"										
AT 22 X 7 - 11	5.5 AT	-	181	557	-	-	STD	4	TL	-
AT 23 X 8 - 11	6.5 AT	6.0 AT	191	594	-	-	STD	4	TL	-
AT 23 X 8 - 11	6.5 AT	6.0 AT	191	594	-	-	STD	6	TL	-
AT 24 X 8 - 11	6.5 AT	6.0 AT	206	610	-	-	STD	4	TL	-
AT 24 X 9 - 11	7.0 AT	7.5 AT	220	605	-	-	STD	4	TL	-
AT 24 X 9 - 11	7.0 AT	7.5 AT	220	605	-	-	STD	6	TL	-
AT 24 X 10 - 11	8.0 AT	7.5 AT; 8.5 AT	254	615	-	-	STD	4	TL	-
12"										
AT 25 X 8 - 12	6.5 AT	6.0 AT	212	630	-	-	STD	4	TL	-
AT 25 X 8 - 12	6.5 AT	6.0 AT	212	630	-	-	STD	6	TL	-
AT 25 X 10 - 12	8.0 AT	6.5 AT; 7.5 AT; 8.5 AT	254	640	-	-	STD	4	TL	-
AT 25 X 10 - 12	8.0 AT	6.5 AT; 7.5 AT; 8.5 AT	254	640	-	-	STD	6	TL	-

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

ATV TIRES



AT 109



AT 109 is suitable for both all-terrain and lawn and garden applications with ATVs. AT 109 is the ideal tire on loose surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
6" AT 145 X 70 - 6	4.5	-	137	366	-	-	STD	2	TL	-
7" AT 16 X 8 - 7	6.5 AT	6.0 AT	183	419	-	-	STD	2	TL	-
8" AT 18 X 9.5 - 8	7.5 AT	8.0 AT	220	468	-	-	STD	2	TL	-
AT 20 X 7 - 8	5.5 AT	6.0 AT	170	504	-	-	STD	2	TL	-
AT 21 X 9 - 8	7.0 AT	6.5 AT; 7.5 AT	222	536	-	-	STD	2	TL	-
AT 22 X 11 - 8	9.0 AT	8.5 AT	230	579	-	-	STD	2	TL	-
9" AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	269	617	-	-	STD	2	TL	-

STD: Standard





AT 110



AT 110 is suitable for both all-terrain and lawn and garden applications with ATVs. AT 110 is the ideal tire on loose surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8"										
AT 20 X 7 - 8	5.5 AT	6.0 AT	183	508	-	-	STD	4	TL	-
9"										
AT 21 X 8 - 9	6.5 AT	6.0 AT	204	541	-	-	STD	4	TL	-
10"										
AT 21 X 7 - 10	5.5 AT	6.0 AT	178	531	-	-	STD	4	TL	-
AT 22 X 8 - 10	6.5 AT	6.0 AT	204	548	-	-	STD	4	TL	-
AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	4	TL	-

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index


ATV TIRES



AT 111



AT 111 is suitable for all-terrain sport applications with ATVs. The tire is ideal for loose surfaces and provides excellent traction in all conditions.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
										
AT 18 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	2	TL	-
AT 18 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
AT 20 X 11 - 8	9.0 AT	8.5 AT	282	508	-	-	STD	6	TL	-
AT 22 X 11 - 8	9.0 AT	8.5 AT	282	508	-	-	STD	6	TL	-
										
AT 18 X 10 - 9	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
AT 20 X 11 - 9	9.0 AT	8.5 AT	279	508	-	-	STD	4	TL	-
AT 20 X 11 - 9	9.0 AT	8.5 AT	279	508	-	-	STD	6	TL	-
AT 22 X 11 - 9	9.0 AT	8.5 AT	282	559	-	-	STD	4	TL	-
AT 22 X 11 - 9	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
										
AT 18 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
AT 19 X 6 - 10	5.0	-	152	472	-	-	STD	4	TL	-
20 X 6 - 10	5.0	-	152	500	-	-	STD	2	TL	-
AT 20 X 6 - 10	5.0	-	152	500	-	-	STD	4	TL	-
AT 20 X 11 - 10	9.0 AT	8.5 AT	275	508	-	-	STD	6	TL	-

STD: Standard



AT 111



SPORT



SUITABLE FOR
LOOSE SURFACE



TRACTION

AT 111 is suitable for all-terrain sport applications with ATVs. The tire is ideal for loose surfaces and provides excellent traction in all conditions.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
10" AT 21 X 7 - 10	5.5 AT	6.0 AT	178	541	-	-	STD	4	TL	-
AT 21 X 7 - 10	5.5 AT	6.0 AT	178	541	-	-	STD	6	TL	-
AT 22 X 7 - 10	5.5 AT	6.0 AT	175	559	-	-	STD	4	TL	-
AT 22 X 11 - 10	9.0 AT	8.5 AT	282	559	-	-	STD	4	TL	-
AT 22 X 11 - 10	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
AT 22 X 7 - 10	5.5 AT	6.0 AT	175	559	-	-	STD	6	TL	-
AT 22 X 8 - 10	6.5 AT	6.0 AT	208	559	-	-	STD	6	TL	-
AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	4	TL	-
AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	6	TL	-

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

ATV TIRES



AT 111 HD



AT 111 HD is suitable for all-terrain sport applications with ATVs on loose surfaces. The increased tread depth and the thick sidewall provide extra grip and braking control in addition to extraordinary traction and high-speed control in power slides. AT 111 HD features outstanding sidewall protection and ensures an extended tire life-cycle.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
9"										
AT 20 X 11 - 9	9.0 AT	8.5 AT	275	515	-	-	HD	6	TL	-
AT 22 X 11 - 9	9.0 AT	8.5 AT	279	560	-	-	HD	6	TL	-
10"										
AT 20 X 11 - 10	9.0 AT	8.5 AT	279	505	-	-	HD	6	TL	-
AT 21 X 7 - 10	5.5 AT	6.0 AT	178	533	-	-	HD	6	TL	-
AT 22 X 7 - 10	5.5 AT	6.0 AT	174	560	-	-	HD	6	TL	-
AT 22 X 11 - 10	9.0 AT	8.5 AT	279	560	-	-	HD	6	TL	-
AT 23 X 7 - 10	5.5 AT	6.0 AT	174	585	-	-	HD	6	TL	-

HD: Heavy Duty Version





AT 119



AT 119 is an all-terrain tire suitable for ATVs. Its tread design provides excellent traction on loose surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8" AT 22 X 11 - 8	9.0 AT	8.5 AT	280	580	-	-	STD	2	TL	-
AT 22 X 11 - 8	9.0 AT	8.5 AT	280	580	-	-	STD	4	TL	-

STD: Standard



BOGMAX



BOGMAX has been specially designed for mud bog racing. The very deep tread pattern ensures excellent traction in extremely wet and muddy conditions whereas the sidewall protectors reduce impacts and possible damages. BOGMAX is a 6-ply-rated tire for extra durability. It also features a cut-and-chip-resistant tread compound and outstanding self-cleaning properties.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
14" 32 X 10 - 14	8.0 AT	4.5 AT; 8.5 AT	250	810	-	-	STD	6	TL	-

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

ATV TIRES



SM 48



SM 48 (GK) has been specially designed for go karts. Its smooth tread design provides excellent performance in sport activities. Shore A hardness 48.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
5" 10 X 4.5 - 5	4.5	-	130	260	-	-	STD	-	TL	-
11 X 7.10 - 5	6.75	-	190	295	-	-	STD	-	TL	-

STD: Standard



SM 54



SM 54 (GK) has been specially designed for go karts. Its smooth tread design provides excellent performance in sport activities. Shore A hardness 54.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
5" 10 X 4.5 - 5	4.5	-	130	260	-	-	STD	-	TL	-
11 X 7.10 - 5	6.75	-	190	295	-	-	STD	-	TL	-

STD: Standard



SM 68



SM 68 has been specially designed for go karts. Its smooth tread design provides excellent performance in sport activities. Shore A hardness 68.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
5" 10 X 4.5 - 5	4.5	-	130	260	-	-	STD	-	TL	-
11 X 6.00 - 5	6.75	-	185	290	-	-	STD	-	TL	-
11 X 7.10 - 5	6.75	-	190	295	-	-	STD	-	TL	-

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

2660 West Market St. Suite 100
Fairlawn (Akron) OH 44333, USA
Tel: (+1) 330 836 1090
Fax: (+1) 330 836 1091
Toll Free: (+1) 888 660 0662

BKT Tires, Inc.

12 Cadillac Drive, Suite 240
Brentwood, Tennessee 37027, USA
Toll Free: (+1) 844 258 8473
Fax: (+1) 330 836 1091

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 905 641 5636
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711