



## EARTHMAX SR 33 - Data Sheet



### Description

Earthmax SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. Earthmax SR 33 provides outstanding stability in addition to best self-cleaning properties. The strong All Steel casing features excellent durability and resistance to snag and punctures.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Universal Vehicle

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
<b>14.00 R 20</b>	STANDARD	164/160 J	10.0	9.0, 10.00W	390	1250	576	3840	TL	E11-54R-0016678
<b>335/80 R 20</b>	STANDARD	150 K	11		335	1047	464	3145	TL	E11-54R-0016679
<b>365/80 R 20 (14.5 R 20)</b>	STANDARD	152 K	11		360	1096	496	3318	TL	E11-54R-0017314
<b>395/85 R 20</b>	STANDARD	168 J	10.00W	10.00HF	394	1184	538	3589	TL	E11-54R-0017315

Printed on 21/02/2024 13:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..