

RIB 900 - Data Sheet



Description

RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire lifecycle.

UM

International Standard

Construction



Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery • Trailer

	SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Туре	ECE
	400/60 - 15.5	STANDARD	139 A8	10	AG 13.00		405	875	380	2564	TL	
	400/60 - 15.5	STANDARD	145 A8	14	AG 13.00		405	875	380	2564	TL	E4-106R-001551
	400/60 - 15.5	STANDARD	147 A8	16	AG 13.00		405	875	380	2564	TL	E4-106R-001548

Printed on 12/02/2024 12:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..