



RIDEMAX FL 690 - Data Sheet

Description

RIDEMAX FL 690 is a radial flotation and transport tire for tank trucks and trailers. The tire is suitable for 75% on-the-road applications. As a response to the increasing demand for high loads in modern agriculture, BKT has designed this steel-belted tire withstanding very heavy loads and increasing the farmer's productivity. The low rolling resistance contributes to better fuel economy.



UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Industrial: Trailer

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
28L R 26 (750/65 R 26)	STANDARD	176 A8/173 B	DW 25 B	DW 23 B	719	1590	695	4745	750	TL	E11-106R-002985
30.5L R 32	STANDARD	184 A8/181 B	DH 27 B	DW 27 B	790	1800	806	5430	875	TL	E11-106R-002986
800/60 R 32	STANDARD	185D	DH 27 B	DW 27 B	800	1800	817	5454	850	TL	E11-106R-006480
VF 900/65 R 32 (VF35.5LR32)	STANDARD	197 D	DW 31 B	DW 30 ; TW 30	930	1986	838	5878	925	TL	E11-106R-006917

Printed on 12/02/2024 14:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..