

XL GRIP (E3) - Data Sheet



Description

XL GRIP (E-3) is a bias-ply tire for rigid dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.00 - 25	STANDARD	E3/L3	28	11.25/2.0	13.00/2.0	465	1485	682	4395	TL
16.00 - 25	STANDARD	E3/L3	32	11.25/2.0	13.00/2.0	465	1485	682	4395	TL
18.00 - 25	STANDARD	E3/L3	24	13.00/2.5	15.00/2.5	510	1615	739	4780	TT
18.00 - 25	STANDARD	E3/L3	32	13.00/2.5	15.00/2.5	510	1615	739	4780	TT
18.00 - 25	STANDARD	E3/L3	32	13.00/2.5	15.00/2.5	510	1615	739	4780	TL
18.00 - 25	STANDARD	E3/L3	40	13.00/2.5	15.00/2.5	510	1615	739	4780	TT
18.00 - 25	STANDARD	E3/L3	40	13.00/2.5	15.00/2.5	510	1615	739	4780	TL
18.00 - 25	STANDARD	E3/L3	16	13.00/2.5	15.00/2.5	510	1615	739	4780	TL
18.00 - 33	STANDARD	E3	32	13.00/2.5		510	1820	840	5385	TT
18.00 - 33	STANDARD	E3	32	13.00/2.5		510	1820	840	5385	TL
18.00 - 33	STANDARD	E3	36	13.00/2.5		510	1820	840	5385	TL
18.00 - 33	STANDARD	E3	40	13.00/2.5		510	1820	840	5385	TL

Printed on 12/02/2024 15:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..