

SOLIDEAL AIR 550

BY CAMSO



INDUSTRIAL
PNEUMATIC



SUPERIOR DURABILITY, PERFORMANCE AND COMFORT

Combining a smooth, comfortable ride with great overall tyre life. Thanks to its unique tread design, superior carcass strength and sidewall protection which makes it the lowest operating cost solution.

camso.co

PERFORMANCE

TYRE LIFE



PUNCTURE RESISTANCE



STABILITY



INDUSTRIAL PNEUMATIC TYRES

SOLIDEAL AIR 550

BY CAMSO

TYRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾	
				Recommended	Alternative
4.00 - 8 (4.80-8)	10	JS2	90-8	3.25I	3.00D
5.00 - 8 (5.70-8)	8	JS2	90-8	3.00D	3.25I/3.75I
16 x 6 - 8 (150/75-8)	14	V3-02-5	130-8	4.33R	-
18 x 7 - 8 (180/70-8)	14	V3-02-5	130-8	4.33R	5.00F
6.50 - 10	12	JS2	140-10	5.00F	5.50F
7.50 - 10	16	JS2	140-10	5.50F	5.00F
23 x 10 - 12 (250/55-12)	16	JS2	210-12	8.00G	-
27 x 10 - 12 (250/75-12)	20	V3-02-5	210-12	8.00G	-
7.00 - 12	16	TR75A	135-12	5.00S	-
355 / 45 - 15 (28x12.5-15)	24	V3-02-10	260-15	9.75	-
355 / 65 - 15 (32x12.1-15)	24	TR78A	260-15	9.75	-
250 - 15 (250/70-15)	16	TR77A	180-15 HD	7,50	7,00
300 - 15 (315/70-15)	22	TR78A	180-15 HD	8,00	-
7.00 - 15	14	TR75A	180-15	5.50	5,00
7.50 - 15	14	TR75A	180-15	6,00	5.50/6.50
7.50 - 16	12	TR75A	180-16	6.0	5.0/5.50
9.00 - 20	14	V3-02-14	200-20	7,00	6.50/7.50
10.00 - 20	16	V3-02-14	200-20	7.50	7.00/8.00
10.00 - 20	20	V3-02-14	200-20	7.50	7.00/8.00
11.00 - 20	16	V3-02-14	200-20	8,00	7.50/8.50
12.00 - 20	20	V3-02-14	200-20	8.50	8.00/9.00
12.00 - 20	28	V3-02-14	200-20	8.50	8.00/9.00

DEEP TREAD LUG WITH ABRASION-RESISTANT RUBBER COMPOUND

- Improves tyre life and provides better traction

UNIQUE TREAD DESIGN WITH FLAT PROFILE

- Increases stability, while reducing vibrations for better comfort



THICK SIDEWALL

- Protects against side impacts causing flat tyres

HEAVY-DUTY CARCASS

- Maximizes tread puncture-resistance to prevent flat tyres

Remarks

- (1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyre are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tyre size

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tyres primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tyres come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tyre availability in your region.

**AVAILABLE IN
NON-MARKING COMPOUND
UPON REQUEST**

