

SOLIDEAL HAULER LT

BY CAMSO



INDUSTRIAL
PNEUMATIC



READY FOR YOUR CHALLENGES.

With a heavy-duty carcass and high abrasion-resistant tread, it delivers both incredible puncture resistance and long life. And with a reinforced sidewall for side impact protection, it's unstoppable.

camso.co

PERFORMANCE

TYRE LIFE



PUNCTURE RESISTANCE



STABILITY



INDUSTRIAL PNEUMATIC

SOLIDEAL HAULER LT

BY CAMSO

TYRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾	
				Recommended	Alternative
5.00-8 (5.70-8)	10	JS2	90-8	3.00D	3.25I/3.75I
16x6-8 (150/75-8)	16	V3-02-05	130-8	4.33R	-
18x7-8 (180/70-8)	16	V3-02-05	130-8	4.33R	5.00F
6.00-9	10	JS2	125-9	4.00E	-
6.00-9	12	JS2	125-9	4.00E	-
21x8-9 (200/75-9)	16	JS2	180-9	6.00E	7.00E
6.50-10	10	JS2	140-10	5.00F	5.50F
6.50-10	12	JS2	140-10	5.00F	5.50F
6.50-10	14	JS2	140-10	5.00F	5.50F
23x9-10 (225/75-10)	20	JS2	180-10	6.50F	-
7.00-12	12	TR75A	135-12	5.00S	-
7.00-12	14	TR75A	135-12	5.00S	-
7.00-12	16	TR75A	135-12	5.00S	-
23x10-12 (250/55-12)	16	JS2	210-12	8.00G	-
27x10-12 (250/75-12)	14	V3-02-05	210-12	8.00G	-
27x10-12 (250/75-12)	20	V3-02-05	210-12	8.00G	-
27x10-12 (250/75-12)	24	V3-02-05	210-12	8.00G	-
7.00-15	14	TR75A	180-15	5.50	5.00
7.50-15	14	TR75A	180-15	6.00	5.50/6.50
28x9-15 (8.15-15 & 225/75-15)	14	V3-02-08	180-15 HD	7.00	-
8.25-15 (7.50-15(32))	14	TR77A	180-15	6.50	6.00/7.00
8.25-15 (7.50-15(32))	16	TR77A	180-15	6.50	6.00/7.00
8.25-15 (7.50-15(32))	18	TR77A	180-15	6.50	6.00/7.00
250-15 (250/70-15)	16	TR77A	180-15 HD	7.50	7.00
250-15 (250/70-15)	20	TR77A	180-15 HD	7.50	7.00
28x12.5-15 (355/45-15)	24	V3-02-10	260-15	9.75	-
300-15 (315/70-15)	18	TR78A	180-15 HD	8.00	-
300-15 (315/70-15)	20	TR78A	180-15 HD	8.00	-
300-15 (315/70-15)	22	TR78A	180-15 HD	8.00	-
32x12.1-15	24	TR78A	260-15	9.75	-
315/85-15	20	TR78A	180-15 HD	7.50	-
10.00-20	16	V3-02-14	200-20	7.50	7.00/8.00
11.00-20	16	V3-02-14	200-20	8.00	7.50/8.50
11.00-20	18	V3-02-14	200-20	8.00	7.50/8.50
12.00-20	18	V3-02-14	200-20	8.50	8.00/9.00
12.00-20	20	V3-02-14	200-20	8.50	8.00/9.00
12.00-20	28	V3-02-14	200-20	8.50	8.00/9.00
14.00-24	28	V3-02-7	250-24	10.00	W/VA/WI
16.00-25	32	TBLS	-	11.25/2.0	13.00/2.0



WIDE SQUARE TREAD PROFILE

- Provides superior stability

MASSIVE TREAD BLOCKS AND DEEP LUGS

- Extends service life in severe applications



WIDE SIDEWALL WITH RIM GUARD

- Provides best side impact resistance
- Three times thicker than standard tyres

REINFORCED UNDERTREAD

- Increases puncture resistance

**AVAILABLE IN
NON-MARKING COMPOUND
UPON REQUEST**



Remarks

(1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyre are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tyre size

** Table shows standard valves. Other valves on request.