

CAMSO TM R4



COMPACT
WHEEL LOADERS



DURABLE OFF-ROAD PERFORMANCE

Provides incomparable durability and traction for heavy-duty applications. Enhanced tread cleanout and lug stability combined to maximize performance.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO TM R4



HAULER STEPPED TREAD DESIGN

- Enhances tread cleanout for improved traction

OPTIMIZED LUG-TO-VOID RATIO

- Enhances longevity and tread puncture resistance



HEAVY-DUTY CARCASS

- Provides excellent stability and side impact resistance

TAPERED TREAD LUGS

- Improves lug stability for even wearing

TIRE SIZE	PR	RIM SIZE		ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	TRA CODE	APPLICATION	MAXIMUM TIRE LOAD [kg]							
		Recom-mended	Alternative	O.D. [mm]	O.W. [mm]	O.T.D. [mm]					Inflation pressure [bar]	Static	5 km/h	10 km/h	15 km/h	25 km/h	40 km/h	50 km/h
18-19.5	16	14.00	13.00	1141	450	28	161	A8	-	-	5.90	7800	6350	6000	5180	-	4625	4480
	20			7.50	9200	7450					7100	6100	-	5450	5280			
405/70-20	16	13	13SDC	1094	406	32	168	A2	-	-	5.00	8900	6350	5550	4825	4450	3875	3500
							150	B			4.00	-	-	-	3750	3625	3450	3350
18-22.5	16	14.00	13.00	1215	450	31	164	A8	-	-	5.90	8450	6850	6500	5600	-	5000	4860
	20			7.50	10100	8200					7800	6700	-	6000	5820			
400/80-24 IND (15.5/80-24)	N/A	DW13	W12; W13; W14L; DW12; DW14L; TW14L	1244	411	37	156	A8	R-4	CYCLIC	4.00	9200	6680*	6000**	5360	4440	4000	3640
										CONSTANT	4.00	9200	5800*	5000**	4520	4240	4000	3640
				CYCLIC	5.00	10925	7935*			7125**	6365	5275	4750	4325				
				CONSTANT	5.00	10925	6890*			5940**	5370	5035	4750	4325				
440/80-24 IND (16.5/85-24)	N/A	DW14L	DW13; DW13L; DW15L; TW13; TW14L; TW15L	1328	453	34	168	A8	R-4	CYCLIC	5.00	12880	9350*	8400**	7505	6215	5600	5095
										CONSTANT	5.00	12880	8120*	7000**	6330	5935	5600	5095
460/70-24 IND (17.5L-24)	N/A	DW15L	DW14L; DW16L; TW14L; TW15L; TW16L	1264	455	34	159	A8	R-4	CYCLIC	4.00	10065	7305*	6565**	5865	4855	4375	3980
										CONSTANT	4.00	10065	6345*	5470**	4945	4640	4375	3980

* Cyclic: One way distance up to 150 m (500 feet)

** Cyclic: One way distance up to 600 m (2000 feet)

