

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)							
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		Speed, km/h (mph)							
								MIXED APPLICATION							
								Static	10	30	40	50	65		
500 60R22.5	AG16.00	503	1172	530	3571	155D	1.2	4390	3440	2880	2600	2310	1910		
							17	9670	7580	6340	5730	5090	4210		
		19.8	46.1	20.9	140.6	155D	1.6	5200	4070	3410	3070	2730	2260		
							23	11450	8960	7510	6760	6010	4980		
									2.4	6600	5170	4330	3900	3470	2870
									35	14540	11390	9540	8590	7640	6320
									2.8	7220	5650	4740	4270	3800	3140
									41	15900	12440	10440	9410	8370	6920
									3.6	8370	6550	5500	4950	4400	3640
									52	18440	14430	12110	10900	9690	8020
4	8910								6980	5850	5270	4690	3875		
58	19630								15370	12890	11610	10330	8540		

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)							
		SW	OD	Radius	mm	Speed		Speed, km/h (mph)							
								MIXED APPLICATION							
		mm	mm	mm	mm	Symbol		Static	10	30	40	50	65		
560 45R22.5 SB*	AG16.00	543	1076	493	3279	152D	1.2	4030	3150	2640	2380	2120	1750		
							17	8880	6940	5810	5240	4670	3850		
		21.4	42.4	19.4	129.1	152D	1.6	4760	3730	3130	2820	2500	2070		
							23	10480	8220	6890	6210	5510	4560		
									2.4	6050	4730	3970	3580	3180	2630
									35	13330	10420	8740	7890	7000	5790
									2.8	6620	5180	4350	3920	3480	2880
									41	14580	11410	9580	8630	7670	6340
									3.6	7680	6010	5040	4540	4040	3340
									52	16920	13240	11100	10000	8900	7360
4	8170								6390	5360	4830	4300	3550		
58	18000								14070	11810	10640	9470	7820		

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in				Recommend load kg /lbs					
560/45R22.5	152D	TL	AG16.00	543 21.4	1076 42.4	493 19.4	3279 129.1	1.2	4030	3150	2640	2380	2120	1750
								1.7	8880	6940	5810	5240	4670	3850
								1.6	4760	3730	3130	2820	2500	2070
								2.3	10480	8220	6890	6210	5510	4560
								2.4	6050	4730	3970	3580	3180	2630
								3.5	13330	10420	8740	7890	7000	5790
								2.8	6620	5180	4350	3920	3480	2880
								4.1	14580	11410	9580	8630	7670	6340
								3.6	7680	6010	5040	4540	4040	3340
								5.2	16920	13240	11100	10000	8900	7360
								4	8170	6390	5360	4830	4300	3550
								5.8	18000	14070	11810	10640	9470	7820

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
								Static	10 6	30 19	40 25	50 31	65 40
560/ 45 R 22.5 FT	AG16.00	543 21.4	1076 42.4	493 19.4	3279 129.1	152D 152D	0.8	3200	2500	2100	1890	1680	1390
							12	7050	5510	4630	4160	3700	3060
							1.6	4780	3740	3140	2830	2520	2080
							23	10530	8240	6920	6230	5550	4580
							2.4	6070	4750	3990	3590	3190	2640
							35	13370	10460	8790	7910	7030	5810
							3.2	7180	5620	4710	4240	3780	3120
							46	15810	12380	10370	9340	8330	6870
							3.6	7680	6010	5040	4540	4040	3340
							52	16920	13240	11100	10000	8900	7360
4	8170	6390	5360	4830	4300	3550							
58	18000	14070	11810	10640	9470	7820							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in					Recommend load kg /lbs				
560/60R22.5	161D	TL	AG16.00	543 21.4	1244 49	561 22.1	3810 150	1.2	5270	4120	3460	3110	2770	2290
								17	11610	9070	7620	6850	6100	5040
								1.6	6230	4880	4090	3690	3280	2710
								23	13720	10750	9010	8130	7220	5970
								2.4	7910	6190	5190	4680	4160	3440
								35	17420	13630	11430	10310	9160	7580
								2.8	8650	6770	5680	5110	4550	3760
								41	19050	14910	12510	11260	10020	8280
								3.6	10010	7830	6570	5920	5260	4350
								52	22050	17250	14470	13040	11590	9580
								4	10640	8330	6980	6290	5600	4625
								58	23440	18350	15370	13850	12330	10190

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
								MIXED APPLICATION					
								mm	mm	mm	mm	mm	mm
560	AG16.00	543	1244	561	3810	164D	0.8	4160	3260	2730	2460	2190	1810
60R22.5 FT		21.4	49.0	22.1	150.0	164D	12	9160	7180	6010	5420	4820	3990
SB*							1.8	6330	4950	4150	3740	3330	2750
							26	13940	10900	9140	8240	7330	6060
							2.8	8190	6410	5380	4840	4310	3560
							41	18040	14120	11850	10660	9490	7840
							3.8	9800	7670	6430	5790	5150	4260
							55	21590	16890	14160	12750	11340	9380
							5	11500	9000	7550	6800	6050	5000
							73	25330	19820	16630	14980	13330	11010

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)								
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		bar psi	Static	Speed, km/h (mph)						
										MIXED APPLICATION						
										10 6	30 19	40 25	50 31	65 40		
580 65R22.5 FT	AG16.00	577	1318	601	3996	166D	0.8	4760	3730	3130	2820	2500	2070			
									12	10480	8220	6890	6210	5510	4560	
									1.6	7130	5580	4680	4220	3750	3100	
		22.7	51.9	23.7	157.3	166D	2.4	9040	7070	5930	5340	4760	3930			
										35	19910	15570	13060	11760	10480	8660
										3.2	10700	8370	7020	6320	5630	4650
							46	23570	18440	15460	13920	12400	10240			
										4	12190	9540	8000	7210	6410	5300
										58	26850	21010	17620	15880	14120	11670

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)							
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		Speed, km/h (mph)							
								bar	Static	MIXED APPLICATION					
										10 6	30 19	40 25	50 31	65 40	
600 50R22.5 FT	AG20.00	611	1172	532	3479	159D	0.8	3930	3080	2580	2330	2070	1710		
							12	8660	6780	5680	5130	4560	3770		
							1.6	5890	4610	3870	3480	3100	2560		
		24.1	46.1	20.9	137.0	159D	23	12970	10150	8520	7670	6830	5640		
							2.4	7480	5850	4910	4420	3930	3250		
							35	16480	12890	10810	9740	8660	7160		
		58	22160	17360	14560	13110	11650	9640	3.2	8830	6910	5800	5220	4650	3840
									46	19450	15220	12780	11500	10240	8460
									4	10060	7880	6610	5950	5290	4375

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in					Recommend load kg /lbs				
600/50R22.5	159D	TL	AG20.00	611	1172	532	3479	1.2	4970	3890	3260	2940	2610	2160
								17	10950	8570	7180	6480	5750	4760
								1.6	5890	4610	3870	3480	3100	2560
								23	12970	10150	8520	7670	6830	5640
								2.4	7450	5830	4890	4410	3920	3240
								35	16410	12840	10770	9710	8630	7140
								2.8	8170	6390	5360	4830	4300	3550
								41	18000	14070	11810	10640	9470	7820
								3.6	9450	7400	6210	5590	4970	4110
								52	20810	16300	13680	12310	10950	9050
								4	10060	7880	6610	5950	5290	4375
								58	22160	17360	14560	13110	11650	9640

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in					Recommend load kg /lbs				
600/55R26.5	165D	TL	AG20.00	620 24.4	1336 52.6	608 24	4050 159.5	1.2	5840	4570	3840	3450	3070	2540
								17	12860	10070	8460	7600	6760	5590
								1.6	6920	5420	4550	4090	3640	3010
								23	15240	11940	10020	9010	8020	6630
								2.4	8790	6880	5770	5200	4620	3820
								35	19360	15150	12710	11450	10180	8410
								2.8	9610	7520	6310	5680	5060	4180
								41	21170	16560	13900	12510	11150	9210
								3.6	11130	8710	7310	6580	5860	4840
								52	24520	19190	16100	14490	12910	10660
								4	11850	9270	7780	7000	6230	5150
								58	26100	20420	17140	15420	13720	11340

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
								Static	10 6	30 19	40 25	50 31	65 40
710/ 45R22.5 FT	AG 24.00	745 29.3	1209 47.6	541 21.3	3661 144.2	165D 165D	0.8	4620	3620	3040	2730	2430	2010
							12	10180	7970	6700	6010	5350	4430
							1.8	7430	5810	4880	4390	3910	3230
							26	16370	12800	10750	9670	8610	7110
							2.6	9200	7200	6040	5440	4840	4000
							38	20260	15860	13300	11980	10660	8810
							3.4	10760	8420	7070	6360	5660	4680
							49	23700	18550	15570	14010	12470	10310
							4	11850	9270	7780	7000	6230	5150
							58	26100	20420	17140	15420	13720	11340

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)												
		SW	OD	Radius	mm	Speed		Speed, km/h (mph)												
								MIXED APPLICATION												
		mm	mm	mm	mm	Symbol		Static	10	30	40	50	65							
600 55R26.5 FT SB*	AG20.00	620	1336	608	4050	165D	0.8	4620	3620	3040	2730	2430	2010							
														24.4	52.6	24.0	159.5	165D	35	19360
		46	22910	17930	15040	13550	12050	9960												
									4	11850	9270	7780	7000							
		58	26100	20420	17140	15420	13720	11340												

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
								Tractor application					
		mm/in	mm/in					Static	10	30	40	50	65
650/ 55 R 26.5 FT	AG20.00	645 25.4	1389 54.7	623 24.5	4207 165.6	178D 178D	0.8	5310	4160	3490	3140	2800	2310
							12	11700	9160	7690	6920	6170	5090
							2	9060	7090	5950	5360	4770	3940
							29	19960	15620	13110	11810	10510	8680
							3	11500	9000	7550	6800	6050	5000
							44	25330	19820	16630	14980	13330	11010
							4	13620	10660	8940	8050	7160	5920
							58	30000	23480	19690	17730	15770	13040
							5	15500	12130	10180	9170	8160	6740
							73	34140	26720	22420	20200	17970	14850
							6.0	17250	13500	11330	10200	9080	7500
							87	38000	29740	24960	22470	20000	16520

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
								Static	10 6	30 19	40 25	50 31	65 40
710/ 50R26.5 FT *SB	AG 24.00	710 28	1383 54.4	621 24.4	4188 164.9	170D 170D	0.8	5360	4190	3520	3170	2820	2330
							12	11810	9230	7750	6980	6210	5130
							1.6	8070	6320	5300	4770	4250	3510
							23	17780	13920	11670	10510	9360	7730
							2.4	10240	8010	6720	6050	5380	4450
							35	22560	17640	14800	13330	11850	9800
							3.2	12120	9490	7960	7170	6380	5270
							46	26700	20900	17530	15790	14050	11610
							4	13800	10800	9060	8160	7260	6000
58	30400	23790	19960	17970	15990	13220							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards