

# REM-8



## (MCS) HIGH-SPEED CRANE TIRE

The REM-8 high-speed crane OTR tire is U.S. DOT approved for on-highway use. The OEM Certified REM-8 is designed with a universal tread pattern to improve traction and deliver a more comfortable ride.



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	TIRE WEIGHT	TIRE TYPE
1117184241	14.00R24 (385/95R24)	REM-8	★★★	70	43	54	16	31	10.00W	13948lb/144psi	133kg/293lb	TL
1117184251	14.00R25 (385/95R25)	REM-8	★★★	70	43	54	16	31	10.00/1.5	13948lb/144psi	135kg/305lb	TL
1117186251	16.00R25 (445/95R25)	REM-8	★★★	70	43	59	17	33	11.25/2.0	16280lb/130psi	209kg/446lb	TL
1117196251	16.00R25 (445/95R25)	REM-8	★★	80	50	59	17	33	11.25/2.0	14740lb/130psi	203kg/444lb	TL
1117190251	20.5R25 (525/80R25)	REM-8	★★	70	43	59	21	39	17.00/2.0	17065.4lb/101psi	238kg/525lb	TL
1117190252	525/80R25 (20.5R25)	REM-8	★★	80	50	59	21	39	17.00/2.0	15620lb/101psi	238kg/525lb	TL

For technical service bulletins please visit Double Coin website