ATU 482 HD

Salient Features

Unique tread pattern to operate in severe applications.

Good self-cleaning properties.

Deeper tread depth for increased service life.

Strong and sturdy heavy duty nylon plies for longer service durability.

Applications

Grader

Skidsteer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		PRESSURE
			REC.INCH	ALT.INCH						30KMPH(Kgs)	40KMPH(Kgs)	(bar)
11L-16	12	TL	8.0	–	830	279	374	2438	120A6/116A8	1400	1250	4.4
11L-16	14	TL	8.0	–	830	279	374	2438	123A6/119A8	1550	1360	4.8
11L-16	16	TL	8.0	–	830	279	374	2438	126A6/122A8	1700	1500	5.2
12.5/80-18	10	TT/TL	W 9	11.0	980	308	438	2896	139A6/135A8	2430	2180	3.1
12.5/80-18	12	TT/TL	W 9	11.0	980	308	438	2896	142A6/138A8	2650	2360	3.7
12.5/80-18	14	TT/TL	W 9	11.0	980	308	438	2896	145A6/141A8	2900	2575	4.3
12.5/80-18	16	TT/TL	W 9	11.0	980	308	438	2896	148A6/144A8	3150	2800	4.9
19.5L-24	12	TL	DW16L	–	1325	490	584	3835	155A6/151A8	3875	3450	2.3
19.5L-24	14	TL	DW16L	–	1325	490	584	3835	158A6/154A8	4250	3750	2.7
19.5L-24	16	TL	DW16L	–	1325	490	584	3835	161A6/157A8	4625	4125	3.0
18.4-26	–	–	–	–	–	–	–	–	–	–	–	–
16.9-28	–	–	–	–	–	–	–	–	–	–	–	–