



Salient Features

- Wide lugs for better grip and handling stability.
- Tough tread compound to resist fast wear.
- Specially designed profile and construction for greater stability.

Applications

Backhoe

Telehandler

SIZES

SIZE	O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	RIM		Bar	1.6	2.0	2.4	2.8	3.0	3.2	3.6	4.0
					REC.INCH	ALT.INCH									
460/70R24 159A8/156B	1254	455	564	3699	DW15L	DW14L	50	2353	2685	2963	3252	3390	3512	3774	4000
							40	2560	2920	3240	3550	3700	3840	4110	4375
							30	2740	3120	3470	3800	3960	4110	4400	4680
							25	2840	3240	3600	3940	4110	4260	4560	4860
							10	3200	3650	4050	4440	4630	4800	5140	5470
500/70R24 164A8/B 19.5L-R24	1310	503	595	3890	DW16L	DW15L, DW18L	50	2400	2850	3250	3700	-	4150	4450	5000
							40	2400	2850	3250	3700	-	4150	4450	5000
							30	2570	3050	3480	3960	-	4445	4765	5350
							25	2665	3165	3610	4110	-	4610	4940	5550
							10	2925	3600	4240	4875	-	5550	6040	6825