



Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

Applications

Baler

Trailer

SIZES

| SIZE | PR | TYPE | RIM | | O.D (mm) | S.W (mm) | SLR (mm) | RC (mm) | LI/SS | MAX. LOAD (LLV) | | INFLATION PRESSURE (bar) | LI/SS | MAX. LOAD (HLV) | | INFLATION PRESSURE (bar) |
|------------|----|-------|----------|----------|----------|----------|----------|---------|---------------|-----------------|--------------|--------------------------|---------------|-----------------|--------------|--------------------------|
| | | | REC.INCH | ALT.INCH | | | | | | 30KMPH (Kgs) | 40KMPH (Kgs) | | | 30KMPH (Kgs) | 40KMPH (Kgs) | |
| 14.0/65-16 | 14 | TT/TL | 11.0 | - | 870 | 353 | 388 | 2549 | 142A6 / 138A8 | 2650 | 2360 | 4.0 | 148A6 / 145A8 | 3150 | 2900 | 5.0 |
| 15.0/55-17 | 10 | TL | 13.0 | 13.0 | 850 | 391 | 379 | 2491 | 134A6 / 130A8 | 2120 | 1900 | 2.6 | 141A6 / 137A8 | 2575 | 2300 | 3.1 |
| 15.0/55-17 | 12 | TL | 13.0 | 13.0 | 850 | 391 | 379 | 2491 | 138A6 / 134A8 | 2360 | 2120 | 3.1 | 144A6 / 140A8 | 2800 | 2500 | 3.7 |
| 15.0/55-17 | 14 | TT/TL | 13.0 | 13.0 | 850 | 391 | 379 | 2491 | 141A6 / 137A8 | 2575 | 2300 | 3.7 | 147A6 / 143A8 | 3075 | 2725 | 4.9 |
| 15.0/55-17 | 18 | TL | 13.0 | 13.0 | 850 | 391 | 379 | 2491 | 146A6 / 142A8 | 3000 | 2650 | 4.4 | 152A6 / 148A8 | 3550 | 3150 | 5.3 |