



## Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

## Applications

Baler

Trailer

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE (bar)	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)			30KMPH (Kgs)	40KMPH (Kgs)	
380/55-17	10	TL	13.0	13.0	850	391	379	2491	134A6 / 130A8	2120	1900	2.6	141A6 / 137A8	2575	2300	3.1
380/55-17	12	TL	13.0	13.0	850	391	379	2491	138A6 / 134A8	2360	2120	3.1	144A6 / 140A8	2800	2500	3.7
480/45-17	14	TL	16.0	-	852	491	380	2530	144A6 / 140A8	2800	2500	2.8	150A6 / 146A8	3350	3000	3.4
480/45-17	16	TL	16.0	-	852	491	380	2530	149A6 / 145A8	3250	2900	3.5	155A6 / 151A8	3875	3450	4.2
480/45-17	18	TL	16.0	-	852	491	380	2530	154A6 / 150A8	3750	3350	3.8	160A6 / 156A8	4500	4000	4.6
500/50-17	14	TL	16.0	-	965	495	406	2712	149A6 / 145A8	3250	2900	2.8	155A6 / 151A8	3875	3450	3.4
500/50-17	16	TL	16.0	-	965	495	406	2712	152A6 / 148A8	3550	3150	3.5	158A6 / 154A8	4250	3750	4.2
500/50-17	18	TL	16.0	-	965	495	406	2712	154A6 / 150A8	3750	3350	4.2	160A6 / 156A8	4500	4000	5.0