



Salient Features

E3 /L3 tread with sturdy loader lug design.

Specially designed, highly durable spec enables increased load capacity.

Deeper tread depth provides enhanced traction.

Special compounding enables less heat generation and additional scrub resistance.

Applications

Dozer

Wheel Loader

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH(Kgs)	40KMPH(Kgs)	
14.00-25	20	TT/TL	10.00/1.5	-	1370	375	635	4040	182 A2	4625	8500	7.0
14.00-25	24	TT/TL	10.00/1.5	-	1370	375	635	4040	186 A2	5150	9500	8.5
14.00-25	28	TT/TL	10.00/1.5	-	1370	375	635	4040	188 A2	5600	10000	9.3
14.00-24	16	TT/TL	10.00 W	-	1370	375	635	4040	177 A2	4000	7300	5.7
14.00-24	20	TL	10.00 W	-	1370	375	635	4040	182A2	4625	8500	7.0
14.00-24	24	TT	10.00 W	-	1370	375	635	4040	186 A2	5150	9500	8.5
14.00-24	28	TT/TL	10.00 W	-	1370	375	635	4040	188 A2	5600	10000	9.3
14.00-24	24	TT/TL	10.00/1.5	-	1370	375	635	4040	186 A2	5150	9500	8.5
14.00-24	28	TT/TL	10.00/1.5	-	1370	375	635	4040	188 A2	5600	10000	9.3