



Salient Features

- Unique lug design with multiple bends for extra surface for higher mileage.
- Extra wide design for heavy duty forklifts and equipments.
- Stronger and tougher body plies for extra load carrying capacity.
- Cuts and cracks resistant tread compound for longer service life.

Applications

Forklift

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH				10KMPH(Kgs)	25KMPH(Kgs)	
18x7-8	10	TT	4.33 R	5.00F	470	173	119A2/116A5	1360	1250	8.0
18x7-8	12	TT	4.33 R	5.00F	470	173	121A2/119A5	1450	1360	8.5
18x7-8	14	TT	4.33 R	5.00F	470	173	123A2/121A5	1550	1450	9.0
18x7-8	16	TT	4.33 R	5.00F	470	173	128A2/125A5	1850	1650	10.0
4.00-8	10	TT	3.25I	3.00D	414	115	100A2/97A5	800	730	10.0
5.00-8	8	TT	3.0D	3.25 I	467	135	109A2/106A5	1030	950	8.3
5.00-8	10	TT	3.0D	3.25 I	467	135	114A2/111A5	1180	1090	10.0
5.00-8	12	TT	3.0D	3.25 I	467	135	117A2/114A5	1285	1180	10.5
6.00-9	10	TT	4.00E	-	544	158	121A2/118A5	1450	1320	8.5
6.00-9	12	TT	4.00E	-	544	158	123A2/121A5	1550	1450	10.0
6.50-10	10	TT	5.00F	5.50F	595	185	124A2/122A5	1600	1500	7.8
6.50-10	12	TT	5.00F	5.50F	595	185	128A2/125A5	1800	1650	9.0
6.50-10	14	TT	5.00F	5.50F	595	185	131A2/128A5	1950	1800	10.0
7.00-12	12	TT	5.00S	-	695	188	136A2/133A5	2240	2060	8.5
7.00-12	14	TT	5.00S	-	695	188	137A2/134A5	2300	2120	9.0
7.00-12	16	TT	5.00S	-	695	188	139A2/136A5	2430	2240	10.0
8.25-15	12	TT	6.5	7	853	236	149A2/146A5	3250	3000	7.0
8.25-15	14	TT	6.5	7	853	236	152A2/149A5	3550	3250	8.0
8.25-15	16	TT	6.5	7	853	236	155A2/152A5	3875	3550	9.3
8.15-15	12	TT	7	7.0BD	722	215	145A2/142A5	2900	2650	8.3
8.15-15	14	TT	7	7.0BD	722	215	148A2/145A5	3150	2900	9.0
8.15-15	16	TT	7	7.0BD	722	215	152A2/149A5	3550	3250	10.5

