



Salient Features

- Unique lug design with multiple bends for extra surface for higher mileage.
- Extra wide design for heavy duty forklifts and equipments.
- Stronger and tougher body plies for extra load carrying capacity.
- Cuts and cracks resistant tread compound for longer service life.

Applications

Forklift

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	LI/SI	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH				10KMPH(Kgs)	25KMPH(Kgs)	
250-15	16	TT	7.5	-	735	250	153A2/150A5	3650	3350	8.3
250-15	18	TT	7.5	-	735	250	156A2/153A5	4000	3650	9.5
250-15	20	TT	7.5	-	735	250	159A2/156A5	4375	4000	10.5
300-15	18	TT	8.0	-	815	300	163A2/160A5	4875	4500	7.5
300-15	20	TT	8.0	-	815	300	166A2/163A5	5300	4875	9.5
7.00-15	12	TT	5.5	-	746	197	141A2/138A5	2575	2360	8.3
7.00-15	14	TT	5.5	-	746	197	144A2/141A5	2800	2575	9.0
7.00-15	16	TT	5.5	-	746	197	145A2/143A5	2900	2725	10.0
7.50-15	12	TT	8.0	-	815	300	145A2/142A5	2900	2650	8.0
7.50-15	14	TT	8.0	-	815	300	146A2/144A5	3000	2800	9.3