



## Salient Features

- Specially designed for golf kart
- Can be used for soil tillage
- Best comfort and ground protection

## Applications

Golf Cart

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	INFLATION PRESSURE
			REC.INCH REC. INCH	ALT.INCH ALT. INCH						(Kgs)	(bar)
15×6.00-6	4	TL	4.5	4.50A	366	155	165	1080	61A2	257	2.1
15×6.00-6	6	TL	4.5	4.50A	366	155	165	1080	70A2	335	3.2
16×6.50-8	4	TL	5.375 I-55	I-70 I-90	406	183	175	1180	64A2	280	1.9
16×6.50-8	6	TL	5.375 I-55	I-70 I-90	406	183	175	1180	72A2	355	2.9
18×8.50-8	4	TL	7.00 I-55	I-70, I-90	450	215	202	1305	74A2	375	1.5
18×8.50-8	6	TL	7.00 I-55	I-70, I-90	450	215	202	1305	82A2	475	2.3
20×10.00-10	4	TL	8	7.00-I-55	508	254	229	1499	86A2	530	1.5
20×10.00-10	6	TL	8	7.00-I-55	508	254	229	1499	93A2	650	2.2
20×10.00-10	12	TL	8	7.00-I-55	508	254	229	1499	106A2	950	3.8
23×10.50-12	4	TL	8.5	7.00-I-55	579	264	261	1708	90A2	600	1.4
23×10.50-12	6	TL	8.5	7.00-I-55	579	264	261	1708	100A2	800	2.2
23×10.50-12	8	TL	8.5	7.00-I-55	579	264	261	1708	106A2	950	3
23×10.50-12	10	TL	8.5	7.00-I-55	579	264	261	1708	111A2	1090	3.8
23×10.50-12	12	TL	8.5	7.00-I-55	579	264	261	1708	115A2	1215	4.2
26×12-12	4	TL	10.5	8.50-I-55	648	307	292	1912	100A2	800	1.4
26×12-12	8	TL	10.5	8.50-I-55	648	307	292	1912	116A2	1250	3
26×12-12	12	TL	10.5	8.50-I-55	648	307	292	1912	124A2	1600	4.5
26×12-12	14	TL	10.5	8.50-I-55	648	307	292	1912	126A2	1700	5.2