



## Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

## Applications

Baler

Trailer

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	INFLATION PRESSURE
			REC.INCH INCH	REC. INCH ALT. INCH						(Kgs)	(bar)
9.5L-14	6	TT/TL	7	8 KB	741	240	326	2154	103 A8/B	875	2.2
9.5L-14	8	TT/TL	7	8 KB	741	240	326	2154	111 A8/B	1090	3.0
9.5L-15	8	TT/TL	7	8LB	767	241	341	2247	112 A8/B	1120	3.0
9.5L-15	10	TT/TL	7	8LB	767	241	341	2247	118 A8/B	1320	3.9
9.5L-15	12	TT/TL	7	8LB	767	241	341	2247	121 A8/B	1450	4.4
10.00-15	8	TT	8	8LB	853	274	375	2499	121 A8/B	1450	2.8
10.00-15	12	TL/TT	8	8LB	853	274	375	2499	128 A8/B	1800	3.9
10.00-15	16	TL/TT	8	8LB	853	274	375	2499	132 A8/B	2000	5.0
11L-15	8	TL/TT	8 LB	10 LB	777	279	342	2300	113 A8/B	1150	2.5
11L-15	10	TL/TT	8 LB	10 LB	777	279	342	2300	118A8/B	1320	3.0
11L-15	12	TL/TT	8 LB	10 LB	777	279	342	2300	121 A8/B	1450	3.6
11L-15	16	TL	8 LB	10 LB	777	279	342	2300	125 A8/B	1650	4.7
7.60-15	8	TL/TT	5.5	6LB	734	193	326	2174	106 B	950	3.6
7.60-15	10	TL	5.5	6LB	734	193	326	2174	110 B	1060	4.3
12.5L-15	8	TT/TL	10 LB	-	823	318	362	2403	119 B	1360	2.5
12.5L-15	10	TT/TL	10 LB	-	823	318	362	2403	123 B	1550	3.0
12.5L-15	12	TT/TL	10 LB	-	823	318	362	2403	127 B	1750	3.6
12.5L-15	14	TT/TL	10 LB	-	823	318	362	2403	130 B	1900	4.4
32×11.50-15	16	TL	10 LB	-	823	318	362	2403	125 A8/B	1650	4.70
31×13.50-15	8	TT/TL	10 LB	-	782	351	362	2315	114B	1180	3.10
31×13.50-15	12	TT/TL	10 LB	-	782	351	362	2315	124B	1600	5.20

