



## Salient Features

- Better traction in all weather conditions.
- Good self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

## Applications

MFWA

## SIZES

| SIZE        | PR | TYPE | RIM      |          | O.D<br>(mm) | S.W<br>(mm) | SLR<br>(mm) | RC<br>(mm) | LI/SS           | MAX. LOAD   |             | PRESSURE<br>(bar) |
|-------------|----|------|----------|----------|-------------|-------------|-------------|------------|-----------------|-------------|-------------|-------------------|
|             |    |      | REC.INCH | ALT.INCH |             |             |             |            |                 | 30KMPH(Kgs) | 40KMPH(Kgs) |                   |
| 11L-15      | 8  | TL   | 8        | -        | 813         | 279         | 366         | 2384       | 110 A6 / 106 A8 | 1060        | 950         | 3.0               |
| 11L-15      | 10 | TL   | 8        | -        | 813         | 279         | 366         | 2384       | 114 A6 / 110 A8 | 1180        | 1060        | 3.6               |
| 11L-15      | 12 | TL   | 8        | -        | 813         | 279         | 366         | 2384       | 117 A6 / 113 A8 | 1285        | 1150        | 4.2               |
| 11L-15      | 22 | TL   | 8        | -        | 813         | 279         | 366         | 2384       | 132A6 / 128A8   | 2000        | 1800        | 6.0               |
| 32x11.50-15 | 22 | TL   | 8        | -        | 813         | 279         | 366         | 2384       | 132A6 / 128A8   | 2000        | 1800        | 6.0               |
| 11L-16S     | 8  | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 112 A6 / 108 A8 | 1120        | 1000        | 3.0               |
| 11L-16S     | 10 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 116 A6 / 112 A8 | 1250        | 1120        | 3.6               |
| 11L-16S     | 12 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 120 A6 / 116 A8 | 1400        | 1250        | 4.4               |
| 11L-16S     | 14 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 123 A6 / 119 A8 | 1550        | 1360        | 4.8               |
| 11L-16P     | 8  | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 112 A6 / 108 A8 | 1120        | 1000        | 3.0               |
| 11L-16P     | 10 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 116 A6 / 112 A8 | 1250        | 1120        | 3.6               |
| 11L-16P     | 12 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 120 A6 / 116 A8 | 1400        | 1250        | 4.4               |
| 11L-16P     | 14 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 123 A6 / 119 A8 | 1550        | 1360        | 4.8               |
| 11L-16P     | 22 | TL   | 8        | -        | 830         | 279         | 374         | 2438       | 132A6 / 128A8   | 2000        | 1800        | 6.0               |