



Salient Features

- Extra Wide and deep shoulder.
- Heavy load carrying capacity and longer life.
- Special compound for economical drive.
- Special compound for less heat generation.

Applications

Light Truck

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD SINGLE		INFLATION PRESSURE		MAX. LOAD DOUBLE		INFLATION PRESSURE	
			REC.INCH	ALT.INCH						100KMPH (Kgs)	-	(bar)	LI/SS	100KMPH (Kgs)	-	(bar)	
6.50-14	8	TT	4.5J	5J	703	176	316	2060	102J	850	-	4.25	100J	800	-	4.25	
6.50-14	10	TT	4.5J	5J	703	176	316	2060	105J	925	-	5.00	103J	875	-	5.00	
7.00-15	12	TT	5.5F	-	769	199	346	2260	114J	1180	-	6.21	109J	1030	-	6.21	
7.00-15	14	TT	5.5F	-	769	199	346	2260	117J	1285	-	-	112J	1120	-	7.20	
7.50-15	12	TT	6.0	6.5	780	211	351	2285	119J	1360	-	6.00	115J	1215	-	6.00	
7.50-15	14	TT	6.0	6.5	780	211	351	2285	121J	1450	-	6.48	118J	1315	-	6.48	
7.00-16	12	TT	5.5F	6.00G	795	199	358	2312	115J	1215	-	6.20	110J	1060	-	6.20	
7.00-16	14	TT	5.5F	6.00G	795	199	358	2312	118J	1320	-	6.90	113J	1150	-	6.90	
7.50-16	14	TT	6.00G	5.50F	824	211	371	2414	122J	1500	-	6.90	118J	1320	-	6.90	
7.50-16	16	TT	6.00G	5.50F	824	211	371	2414	124J	1600	-	7.60	120J	1400	-	7.60	
8.25-16	16	TT	6.50H	6.00G	863	234	379	2529	129J	1850	-	7.60	127J	1750	-	7.60	