

ML 869 (M88)



Salient Features

- Designed for on and off the road farm services.
- Good traction on soft and sandy terrain.
- Very effective design for haulage purpose.
- All wheel fitment.

Applications

Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (Kgs)	INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH							
6.00-16M	8	TT	4.5E	-	731	166	329	2142	93 F	650	2.8
9.00-16	8	TT	6.5 H	6.00 G	903	251	422	2673	118 F	1320	3.1
9.00-16	16	TT	6.5 H	6.00 G	903	251	422	2673	134 F	2120	7.3
7.00-16	6	TT	5.50F	-	781	197	356	2297	101 F	825	2.8
7.00-16	8	TT	5.50F	-	781	197	356	2297	107 F	975	3.8
7.50-16	8	TT	5.50F	-	813	211	383	2412	112 F	1120	3.8
7.50-16	12	TT	5.50F	-	813	211	383	2412	120 F	1400	5.9
7.50-16	14	TT	5.50F	-	813	211	383	2412	122 F	1500	6.9
7.50-20	8	TT	6.00	5.5F	940	213	423	2754	116 F	1250	5.0
7.50-20	10	TT	6.00	5.5F	940	213	423	2754	120 F	1400	5.5
7.50-20	14	TT	6.00	5.5F	940	213	423	2754	126 F	1700	7.6
9.00-20	12	TT	7.00	6.5	1029	257	463	3025	133 F	2060	5.9