



## Salient Features

- Good Traction in all weather conditions.
- Good self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

## Applications

Trailer

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SI	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH(Kgs)	40KMPH(Kgs)	
10.0/75-15.3	10	TL	9.0	-	774	258	355	2310	127A6 / 123A8	1750	1550	3.9
10.0/75-15.3	12	TL	9.0	-	774	258	355	2310	130A6 / 126A8	1900	1700	4.7
10.0/75-15.3	14	TL	9.0	-	774	258	355	2310	134A6 / 130A8	2120	1900	5.5
10.0/75-15.3	18	TL	9.0	-	774	258	355	2310	139A6 / 135A8	2430	2180	7.1
11.5/80-15.3	10	TL	9.0	-	868	292	393	2578	135A6 / 131A8	2180	1950	3.4
11.5/80-15.3	14	TL	9.0	-	868	292	393	2578	143A6 / 139A8	2725	2430	4.8
11.5/80-15.3	18	TL	9.0	-	868	292	393	2578	147A6 / 143A8	3075	2725	6.0

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SI	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH						40KMPH(Kgs)	65KMPH(Kgs)	
10.5-18	10	TT/TL	9	9 SDC	905	270	415	2700	131A8 / 126G	1950	1700	3.8
10.5-18	12	TL	9	9 SDC	905	270	415	2700	135A8 / 131G	2180	1950	4.5
10.5-18	14	TL	9	9 SDC	905	270	415	2700	137A8 / 133G	2300	2060	5.0
12.5-18	10	TT/TL	11	12 SDC	990	325	450	2940	133A8 / 128G	2060	1800	3.0
12.5-18	12	TT/TL	11	12 SDC	990	325	450	2940	136A8 / 131G	2240	1950	3.5
10.5-20	10	TT/TL	9	9 SDC	955	270	445	2880	133A8 / 128G	2060	1800	3.8
12.5-20	10	TT/TL	11	12 SDC	1040	325	475	3090	134 A8 / 129 G	2120	1850	3.0
12.5-20	12	TT/TL	11	12 SDC	1040	325	475	3090	137A8 / 132G	2300	2000	3.5
12.5-20	14	TL	11	12 SDC	1040	325	475	3090	139A8 / 134G	2430	2120	4.0
12.5-20	16	TL	11	12 SDC	1040	325	475	3090	141A8 / 136G	2575	2240	4.5