



Salient Features

- Multi-angled curved lug-bars for improved traction and self-cleaning.
- Longer continuity of lug bars in contact patch for comfort driving.
- Strong and sturdy body plies for longer service durability, even on haulage.
- Cut and crack resistant tread compound for longer service life.

Applications

2WD Tractor

4WD Tractor

MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
8.00-20	6	TT	W6	5.50 F	956	238	419	2670	96A6/92A8	710	630	2.4
8.3-20	6	TT	W6	5.50F	956	238	419	2670	96A6/92A8	710	630	2.4
8.3-20	8	TT	W6	5.50F	956	238	419	2670	101A6/98A8	825	750	3.2
9.5-20	6	TT	W8	W7	956	238	435	2670	102A6/99A8	850	775	2.2
9.5-20	8	TT	W8	W7	956	238	435	2670	107A6/103A8	975	875	2.8
9.5-20	12	TT	W8	W7	956	238	435	2670	112A6/108A8	1120	1000	3.6
11.2-20	8	TT	W10	W9	1020	292	470	2995	111A6/107A8	1090	975	2.4
8.3-22	6	TT	W7	-	956	238	432	2670	98A6/94A8	750	670	2.6
8.3-22	8	TT	W7	-	956	238	432	2670	104A6/100A8	900	800	3.2
9.5-22	8	TT	8.0	W7	1020	244	457	2955	110A6/106A8	1060	950	2.9
8.3-24	6	TT	W7	W6	995	211	469	2925	100A6/96A8	800	710	2.4
8.3-24	8	TT	W7	W6	995	211	469	2925	105A6/101A8	925	825	3.1
8.3-24	10	TT	W7	W6	995	211	469	2925	107A6/103A8	975	875	3.4
8.3-24	12	TT	W7	W6	995	211	469	2925	111A6/107A8	1090	975	4.0
8.3-24	14	TT	W7	W6	995	211	469	2925	115A6/111A8	1215	1090	4.8
9.5-24	6	TT	W8	W7	1056	232	495	3105	106A6/102A8	950	850	2.1
9.5-24	8	TT	W8	W7	1056	232	495	3105	112A6/108A8	1120	1000	2.8
9.5-24	10	TT	W8	W7	1056	232	495	3105	117A6/113A8	1285	1120	3.4
9.5-24	12	TT	W8	W7	1056	232	495	3105	120A6/116A8	1400	1250	4.2
9.5-24	14	TT	W8	W7	1056	232	495	3105	123A6/120A8	1550	1400	4.9
11.2-24	6	TT/TL	W10	W9	1105	284	515	3249	110A6/106A8	1060	950	1.8

MRT 329



11.2-24	8	TT	W10	W9	1105	284	515	3249	116A6/112A8	1250	1120	2.4
11.2-24	10	TT	W10	W9	1105	284	515	3249	120A6/116A8	1400	1250	3.0
11.2-24	12	TT	W10	W9	1105	284	515	3249	122A6/119A8	1500	1360	3.2
11.2-24	14	TT	W10	W9	1105	284	515	3249	124A6/121A8	1600	1450	3.6
12.4-24	6	TT	W11	W9, W10	1160	315	539	3410	115A6/111A8	1215	1090	1.7
12.4-24	8	TT/TL	W11	W9, W10	1160	315	539	3410	121A6/117A8	1450	1285	2.3
12.4-24	10	TT/TL	W11	W9, W10	1160	315	539	3410	124A6/121A8	1600	1450	2.9
12.4-24	12	TT/TL	W11	W9, W10	1160	315	539	3410	128A6/124A8	1800	1600	3.5
12.4-24	14	TT/TL	W11	W9, W10	1160	315	539	3410	130A6/126A8	1900	1700	4.2
13.6-24	6	TT	W12	W11	1209	345	559	3556	119A6/115A8	1360	1215	1.6
13.6-24	8	TT	W12	W11	1209	345	559	3556	123A6/120A8	1550	1400	1.9
13.6-24	10	TT	W12	W11	1209	345	559	3556	126A6/122A8	1700	1550	2.5
13.6-24	12	TT	W12	W11	1209	345	559	3556	130A6/126A8	1900	1700	2.9
13.6-24	14	TT	W12	W11	1209	345	559	3556	133A6/129A8	2060	1850	3.2
14.9-24	4	TT	W13	W11, W12	1265	378	584	3710	112A6/109A8	1120	1030	0.8
14.9-24	6	TT	W13	W11, W12	1265	378	584	3710	123A6/119A8	1550	1360	1.4
14.9-24	8	TT/TL	W13	W11, W12	1265	378	583	3710	128A6/124A8	1800	1600	1.8
14.9-24	10	TT	W13	W11, W12	1265	378	583	3710	132A6/128A8	2000	1800	2.3
14.9-24	12	TT	W13	W11, W12	1265	378	583	3710	135A6/132A8	2180	2000	2.6
14.9-24	14	TT	W13	W11, W12	1265	378	583	3710	138A6/135A8	2360	2180	3.0
16.9-24	6	TT	15.0	-	1335	429	615	3950	126A6/123A8	1700	1550	1.3
16.9-24	8	TT	15.0	-	1335	429	615	3950	133A6/129A8	2060	1850	1.7
16.9-24	10	TT	15.0	-	1335	429	615	3950	136A6/132A8	2240	2000	1.9
16.9-24	12	TT	15.0	-	1335	429	615	3950	140A6/136A8	2500	2240	2.4
16.9-24	14	TT	15.0	-	1335	429	615	3950	142A6/138A8	2650	2360	2.7
14.9-26	8	TT	W12	DW12A	1316	378	605	3895	129A6/125A8	1850	1650	1.8
14.9-26	12	TT	W12	DW12A	1316	378	605	3895	136A6/132A8	2240	2000	2.6
14.9-26	14	TT	W12	DW12A	1316	378	605	3895	139A6/135A8	2430	2180	3.2
16.9-26	8	TT	W14L	-	1380	429	635	4065	133A6/129A8	2060	1850	1.7
16.9-26	10	TT	W14L	-	1380	429	635	4065	137A6/133A8	2300	2060	1.9
16.9-26	12	TT	W14L	-	1380	429	635	4065	140A6/137A8	2500	2300	2.4
16.9-26	14	TT	W14L	-	1380	429	635	4065	143A6/139A8	2725	2430	2.8
18.4-26	8	TT/TL	W16L	W15L	1450	467	662	4278	137A6/133A8	2300	2060	1.5
18.4-26	10	TT/TL	W16L	W15L	1450	467	662	4278	142A6/138A8	2650	2360	1.8
18.4-26	12	TT	W16L	W15L	1450	467	662	4278	146A6/142A8	3000	2650	2.3
18.4-26	14	TT	W16L	W15L	1450	467	662	4278	150A6/146A8	3350	3000	2.8
18.4-26	16	TT	W16L	W15L	1450	467	662	4278	152A6/148A8	3550	3150	3.2
23.1-26	10	TT	20.0	DW20A	1605	587	738	4751	149A6/145A8	3250	2900	1.4
23.1-26	12	TT	20.0	DW20A	1605	587	738	4751	153A6/149A8	3650	3250	1.7
23.1-26	14	TT	20.0	DW20A	1605	587	738	4751	156A6/152A8	4000	3550	1.9
23.1-26	16	TT	20.0	DW20A	1605	587	738	4751	159A6/155A8	4375	3875	2.3
23.1-26	18	TT/TL	20.0	DW20A	1605	587	738	4751	161A6/157A8	4625	4125	2.6
11.2-28	6	TT/TL	W10	W9	1205	284	563	3530	112A6/108A8	1120	1000	1.8
11.2-28	8	TT	W10	W9	1205	284	563	3530	118A6/114A8	1320	1180	2.4
11.2-28	10	TT	W10	W9	1205	284	563	3530	122A6/118A8	1500	1320	2.7
11.2-28	12	TT	W10	W9	1205	284	563	3530	125A6/121A8	1650	1450	3.2
11.2-28	14	TT	W10	W9	1205	284	563	3530	128A6/124A8	1800	1600	3.5
12.4-28	6	TT/TL	W11	W9, W10	1260	315	589	3704	117A6/113A8	1285	1150	1.7
12.4-28	8	TT/TL	W11	W9, W10	1260	315	589	3704	123A6/120A8	1550	1400	2.3

MRT 329



12.4-28	10	TT	W11	W9, W10	1260	315	589	3704	124A6/120A8	1600	1400	2.4
12.4-28	12	TT	W11	W9, W10	1260	315	589	3704	125A6/121A8	1650	1450	2.5
12.4-28	14	TT	W11	W9, W10	1260	315	589	3704	126A6/122A8	1700	1500	2.6
13.6-28	6	TT	W12	W11	1310	345	610	3851	121A6/117A8	1450	1285	1.5
13.6-28	8	TT/TL	W12	W11	1310	345	610	3851	125A6/121A8	1650	1450	2.0
13.6-28	10	TT	W12	W11	1310	345	610	3851	127A6/123A8	1750	1575	2.2
13.6-28	12	TT	W12	W11	1310	345	610	3851	128A6/124A8	1800	1600	2.3
13.6-28	14	TT	W12	W11	1310	345	610	3851	129A6/125A8	1850	1650	3.5
14.9-28	8	TT/TL	W13	W11, W12	1365	378	634	4013	130A6/126A8	1900	1700	1.8
14.9-28	10	TT	W13	W11, W12	1365	378	634	4013	132A6/128A8	2000	1800	2.1
14.9-28	12	TT	W13	W11, W12	1365	378	634	4013	134A6/130A8	2120	1900	2.3
14.9-28	14	TT	W13	W11, W12	1365	378	634	4013	136A6/132A8	2240	2000	2.6
16.9-28	8	TT	W15L	W14L	1435	429	655	4310	135A6/131A8	2180	1950	1.7
16.9-28	10	TT	W15L	W14L	1435	429	655	4310	139A6/135A8	2430	2180	2.0
16.9-28	12	TT	W15L	W14L	1435	429	655	4310	143A6/139A8	2725	2430	2.4
16.9-28	14	TT	W15L	W14L	1435	429	655	4310	146A6/142A8	3000	2650	2.8
18.4-28	8	TT	16.0	-	1501	467	687	4428	138A6/134A8	2360	2120	1.4
18.4-28	10	TT	16.0	-	1501	467	687	4428	143A6/139A8	2725	2430	1.8
18.4-28	12	TT	16.0	-	1501	467	687	4428	147A6/143A8	3075	2725	2.2
18.4-28	14	TT	16.0	-	1501	467	687	4428	150A6/146A8	3350	3000	2.6
14.9-30	6	TT	W13	W11, W12	1415	378	659	4316	126A6/122A8	1700	1500	1.4
14.9-30	8	TT	W13	W11, W12	1415	378	659	4316	131A6/127A8	1950	1750	1.8
14.9-30	10	TT	W13	W11, W12	1415	378	659	4316	135A6/131A8	2180	1950	2.2
14.9-30	12	TT	W13	W11, W12	1415	378	659	4316	138A6/134A8	2360	2120	2.5
14.9-30	14	TT	W13	W11, W12	1415	378	659	4316	141A6/137A8	2575	2300	2.8
16.9-30	8	TT	W15L	W14L	1485	429	685	4381	137A6/132A8	2300	2000	1.7
16.9-30	10	TT	W15L	W14L	1485	429	685	4381	140A6/136A8	2500	2240	2.0
16.9-30	12	TT	W15L	W14L	1485	429	685	4381	144A6/140A8	2800	2500	2.4
16.9-30	14	TT	W15L	W14L	1485	429	685	4381	146A6/142A8	3000	2650	2.8
18.4-30	8	TT	W16L	W15L	1545	467	714	4542	139A6/135A8	2430	2180	1.4
18.4-30	10	TT	W16L	W15L	1545	467	714	4542	145A6/141A8	2900	2575	1.8
18.4-30	12	TT	W16L	W 15 L	1545	467	714	4542	149A6/145A8	3250	2900	2.3
18.4-30	14	TT	W16L	W15L	1545	467	714	4542	151A6/147A8	3450	3075	2.6
23.1-30	8	TT	20.0	DW20A	1707	587	785	5053	147A6/143A8	3075	2725	1.1
23.1-30	12	TT/TL	20.0	DW20A	1707	587	785	5053	155A6/151A8	3875	3450	1.7
23.1-30	14	TT/TL	20.0	DW20A	1707	587	785	5053	158A6/154A8	4250	3750	2.1
23.1-30	16	TT/TL	20.0	DW20A	1707	587	785	5053	162A6/158A8	4750	4250	2.3
23.1-30	18	TT/TL	20.0	DW20A	1707	587	785	5053	164A6/160A6	5000	4500	2.6
12.4-32	8	TT	W11	W9, W10	1360	325	639	3998	125A6/121A8	1650	1450	2.2
12.4-32	10	TT	W11	W9, W10	1360	325	639	3998	128A6/124A8	1800	1600	2.5
12.4-32	12	TT	W11	W9, W10	1360	325	639	3998	131A6/127A8	1950	1750	2.9
12.4-32	14	TT	W11	W9, W10	1360	325	639	3998	133A6/130A8	2060	1900	3.1
16.9-34	8	TT	W15L	W14L	1585	429	735	4650	138A6/134A8	2360	2120	1.7
16.9-34	10	TT	W15L	W14L	1585	429	735	4650	142A6/138A8	2650	2360	2.0
16.9-34	12	TT	W15L	W14L	1585	429	735	4650	144A6/140A8	2800	2500	2.3
16.9-34	14	TT	W15L	W14L	1585	429	735	4650	146A6/142A8	3000	2650	2.5
18.4-34	8	TT	W16L	W15L	1650	467	762	4850	142A6/138A8	2650	2360	1.4
18.4-34	10	TT	W16L	W15L	1650	467	762	4850	146A6/143A8	3000	2725	1.8
18.4-34	12	TT	W16L	W15L	1650	467	762	4850	150A6/146A8	3350	3000	2.3

18.4-34	14	TT/TL	W16L	W15L	1650	467	762	4850	154A6/150A8	3750	3350	2.6
20.8-34	8	TT	W18L	-	1732	528	797	5109	146A6/142A8	3000	2650	1.3
20.8-34	10	TT	W18L	-	1732	528	797	5109	150A6/146A8	3350	3000	1.5
20.8-34	12	TT	W18L	-	1732	528	797	5109	154A6/150A8	3750	3350	1.8
20.8-34	14	TT	W18L	-	1732	528	797	5109	156A6/153A8	4000	3650	2.1
12.4-36	8	TT	W11	W9, W10	1465	315	686	4318	127A6/123A8	1750	1550	2.3
12.4-36	10	TT	W11	W9, W10	1465	315	686	4318	131A6/127A8	1950	1750	2.9
12.4-36	12	TT	W11	W9, W10	1465	315	686	4318	135A6/131A8	2180	1950	3.5
12.4-36	14	TT	W11	W9, W10	1465	315	686	4318	139A6/135A8	2430	2180	4.1
13.6-36	6	TT	W12	W11	1515	345	710	4445	125A6/121A8	1650	1450	1.5
13.6-36	8	TT	W12	W11	1515	345	710	4445	131A6/127A8	1950	1750	2.1
13.6-36	10	TT	W12	W11	1515	345	710	4445	135A6/131A8	2180	1950	2.5
13.6-36	12	TT	W12	W11	1515	345	710	4445	139A6/135A8	2430	2180	3.0
13.6-36	14	TT	W12	W11	1515	345	710	4445	143A6/139A8	2725	2430	3.5
12.4-38	6	TT	W11	W9, W10	1524	315	710	4496	122A6/118A8	1500	1320	1.7
12.4-38	8	TT	W11	W9, W10	1524	315	710	4496	127A6/123A8	1750	1550	2.3
12.4-38	10	TT	W11	W9, W10	1524	315	710	4496	131A6/127A8	1950	1750	2.7
12.4-38	12	TT	W11	W9, W10	1524	315	710	4496	135A6/131A8	2180	1950	3.3
12.4-38	14	TT	W11	W9, W10	1524	315	710	4496	138A6/134A8	2360	2120	3.7
13.6-38	8	TT	W12	W11	1565	345	738	4601	131A6/127A8	1950	1750	2.0
13.6-38	10	TT	W12	W11	1565	345	738	4601	133A6/129A8	2060	1850	2.2
13.6-38	12	TT	W12	W11	1565	345	738	4601	139A6/135A8	2430	2180	2.9
13.6-38	14	TT	W12	W11	1565	345	738	4601	141A6/137A8	2575	2300	3.1
14.00-38	8	TT	W12	W11	1565	345	738	4601	131A6/127A8	1950	1750	2.0
14.00-38	10	TT	W12	W11	1565	345	738	4601	135A6/131A8	2180	1950	2.5
14.00-38	12	TT	W12	W11	1565	345	738	4601	139A6/135A8	2430	2180	3.0
14.00-38	14	TT	W12	W11	1565	345	738	4601	142A6/138A8	2650	2360	3.5
15.5-38	8	TT	W14L	-	1585	394	746	4660	133A6/129A8	2060	1850	1.8
15.5-38	10	TT	W14L	-	1585	394	746	4660	135A6/131A8	2180	1950	2.1
15.5-38	12	TT	W14L	-	1585	394	746	4660	140A6/136A8	2500	2240	2.4
15.5-38	14	TT	W14L	-	1585	394	746	4660	142A6/138A8	2650	2360	2.6
16.9-38	8	TT	W15L	W14L	1685	429	788	4954	141A6/136A8	2575	2240	1.7
16.9-38	10	TT	W15L	W14L	1685	429	788	4954	143A6/139A8	2725	2430	2.1
16.9-38	12	TT	W15L	W14L	1685	429	788	4954	146A6/142A8	3000	2650	2.3
16.9-38	14	TT	W15L	W14L	1685	429	788	4954	148A6/144A8	3150	2800	3.0
18.4-38	8	TT	W16L	W15L	1750	467	812	5163	143A6/139A8	2725	2430	1.4
18.4-38	10	TT	W16L	W15L	1750	467	812	5163	149A6/145A8	3250	2900	1.8
18.4-38	12	TT	W16L	W15L	1750	467	812	5163	153A6/149A8	3650	3250	2.3
18.4-38	14	TT	W16L	W15L	1750	467	812	5163	154A6/150A8	3750	3350	2.5
20.8-38	8	TT	W18L	W16L	1835	530	852	5395	148A6/144A8	3150	2800	1.3
20.8-38	10	TT/TL	W18L	W16L	1835	530	852	5395	152A6/148A8	3550	3150	1.7
20.8-38	12	TT	W18L	W16L	1835	530	852	5395	156A6/152A8	4000	3550	2.0
20.8-38	14	TT	W18L	W16L	1835	530	852	5395	159A6/155A8	4375	3875	2.4
20.8-38	16	TT	W18L	W16L	1835	530	852	5395	161A6/157A8	4625	4125	2.8