



Salient Features

- Unique and broader lug design
- Strong casing
- Better Penetration into the soil
- Self-cleaning property of the tyre

Applications

2WD Tractor

MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
14.9-26	8	TT	W12	DW12A	1316	378	605	3895	129 A6/125A8	1850	1650	1.8
14.9-26	10	TT	W12	DW12A	1316	378	605	3895	133A6/129A8	2060	1850	2.2
14.9-26	12	TT	W12	DW12A	1316	378	605	3895	136A6/132A8	2240	2000	2.6
14.9-26	14	TT	W12	DW12A	1316	378	605	3895	139A6/135A8	2430	2180	3.2
12.4-28	8	TT	W 11	W 9, W 10	1270	315	589	3704	123 A6 / 120 A8	1550	1400	2.3
12.4-28	10	TT	W 11	W 9, W 10	1270	315	589	3704	124 A6 / 120 A8	1600	1400	2.4
12.4-28	12	TT	W 11	W 9, W 10	1270	315	589	3704	125 A6 / 121 A8	1650	1450	2.5
12.4-28	14	TT	W 11	W 9, W 10	1270	315	589	3704	126 A6 / 122 A8	1700	1500	2.6
13.6-28	8	TT	W 12	-	1310	345	610	3851	125 A6 / 121 A8	1650	1450	2.0
13.6-28	10	TT	W 12	-	1310	345	610	3851	127 A6 / 123 A8	1750	1550	2.2
13.6-28	12	TT	W 12	-	1310	345	610	3851	128A6/124A8	1800	1600	2.3
13.6-28	14	TT	W 12	-	1310	345	610	3851	129A6/125A8	1850	1650	2.4