



Salient Features

- Multi-angled curved lug-bars for improved traction and self-cleaning.
- Longer continuity of lug bars in contact patch for comfort driving.
- Strong and sturdy body plies for longer service durability, even on haulage.
- Cut and crack resistant tread compound for longer service life.

Applications

2WD Tractor

4WD Tractor

MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
8.00-18	8	TT	W7	-	835	206	385	2465	98 A6	750	-	2.1
8.00-18	12	TT	W7	-	835	206	385	2465	102 A6	850	-	2.1
12.4-28	8	TT	W 11	W 9, W 10	1260	315	589	3704	123 A6 / 120 A8	1550	1400	2.3
12.4-28	10	TT	W 11	W 9, W 10	1260	315	589	3704	124 A6 / 120 A8	1600	1400	2.4
12.4-28	12	TT	W 11	W 9, W 10	1260	315	589	3704	125 A6 / 121 A8	1650	1450	2.5
12.4-28	14	TT	W 11	W 9, W 10	1260	315	589	3704	126 A6 / 122 A8	1700	1500	2.6
18.4-30	8	TT	W16L	W 15 L	1545	460	714	4542	139 A6 / 135 A8	2430	2180	1.4
18.4-30	10	TT	W16L	W 15 L	1545	460	714	4542	145 A6 / 140 A8	2900	2500	1.8
18.4-30	12	TT	W16L	W 15 L	1545	460	714	4542	149 A6 / 145 A8	3250	2900	2.3
18.4-30	14	TT	W16L	W 15 L	1545	460	714	4542	151 A6 / 147 A8	3450	3075	2.6