



Salient Features

Specially profiled central rib for deeper penetration and better steering control.

Adequately reinforced rib base for minimum lateral side-slipping.

Strong and sturdy body plies for longer service durability.

Cut and crack resistant tread compound for increased service life.

Applications

2WD Tractor

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
4.00-8	4	TT	3.0	2.50 C	435	112	200	1288	43A6 / 35A8	155	121	2.4
4.00-12	4	TT/TL	3.0 D	2.50 C	530	112	251	1570	60 A6 / 52 A8	250	200	3.4
4.00-12	6	TT	3.0 D	2.50 C	530	112	251	1570	68 A6 / 60 A8	315	250	4.1
5.00-15	4	TT/TL	4.0E	3.00D, 4J, 4½ J	655	140	306	1952	73 A6 / 65 A8	365	290	2.8
5.00-15	6	TL	4.0E	3.00D, 4J, 4½ J	655	140	306	1952	82A6/74A8	475	375	3.7
5.00-15	8	TT/TL	4.0E	3.00D, 4J, 4½ J	655	140	306	1952	86A6/78A8	530	425	4.5
9.5L-15	8	TL	7.0	8 LB	780	240	359	2330	106A6/102A8	950	850	3.3
9.5L-15	10	TT	7.0	8 LB	780	240	359	2330	110A6/106A8	1060	950	4.0
11L-15	8	TL	8 LB	10 LB	795	279	380	2370	110A6/106A8	1060	950	3.0
11L-15	10	TL	8 LB	10 LB	795	279	380	2370	114A6/110A8	1180	1060	3.6
5.50-16	4	TL	4.0E	3.50 D, 4.50 E	710	150	331	2116	78 A6 / 70 A8	425	335	2.5
5.50-16	6	TL	4.0E	3.50 D, 4.50 E	710	150	331	2116	86 A6 / 78 A8	530	425	3.7
5.50-16	8	TT/TL	4.0E	3.50 D, 4.50 E	710	150	331	2116	92 A6 / 84 A8	630	500	4.5
6.00-16DBG	6	TT	4.5 E	4.00 E, 5 K, 5.00 F	740	165	355	2190	88 A6 / 80 A8	560	450	3.3
6.00-16DBG	8	TT/TL	4.5E	4.00 E, 5 K, 5.00 F	740	165	355	2190	94 A6 / 86 A8	670	530	4.5
6.00-16DBG	10	TL	4.5 E	4.00 E, 5 K, 5.00 F	740	165	355	2190	98 A6 / 90 A8	750	600	5.0
6.50-16	6	TT	4.5E	4.00 E, 5 K, 5.00 F 5.50 F	760	175	359	2280	91 A6 / 83 A8	615	487	3.1
6.50-16	8	TT/TL	4.5E	4.00 E, 5 K, 5.00 F 5.50 F	760	175	359	2280	98 A6 / 90 A8	750	600	4.2
7.50-16	6	TT	5.5 F	5.00 F, 5 K, 6.00 F	805	205	370	2413	98 A6 / 90 A8	750	600	2.8

MTF 212



7.50-16	8	TT/TL	5.5F	5.00 F, 5 K, 6.00 F	805	205	370	2413	103 A6 / 96 A8	875	710	3.7
7.50-16	10	TT/TL	5.5 F	5.00 F, 5 K, 6.00 F	805	205	370	2413	109 A6 / 101 A8	1030	825	4.8
10.00-16	8	TT/TL	W 8	W 8 L	895	274	408	2692	115 A6 / 107 A8	1215	975	2.8
10.00-16	10	TT/TL	W8	W 8 L	895	274	408	2692	119 A6 / 111 A8	1360	1090	3.4
10.00-16	12	TT	W8	W 8 L	895	274	408	2692	122A6/114A8	1500	1180	4.0
11.00-16	8	TT/TL	W 10 L	W 8, W 8 L	965	315	457	2895	118 A6 / 110 A8	1320	1060	2.5
11.00-16	10	TT/TL	W 10 L	W 8, W 8 L	965	315	457	2895	122 A6 / 115 A8	1500	1215	3.1
11.00-16	12	TT/TL	W 10 L	W 8, W 8 L	965	315	457	2895	126A6 / 123A8	1700	1550	3.6
14L-16.1	10	TT	W11C	-	980	356	447	2921	127A6/123A8	1750	1550	3.0
14L-16.1	12	TL	W11C	-	980	356	447	2921	131A6/127A8	1950	1750	3.6
14L-16.1	14	TT	W11C	-	980	356	447	2921	133A6/129A8	1950	1850	4.1
9.00-16	8	TT/TL	W 8	6.00 F, W 7,W 8 L	855	234	405	2548	111 A6 / 103 A8	1090	875	3.1
9.00-16	10	TT/TL	W 8	6.00 F, W 7,W 8 L	855	234	405	2548	116 A6 / 108 A8	1250	1000	3.9
7.50-18	8	TT/TL	5.5 F	-	874	208	405	2615	106 A6 / 98 A8	950	750	3.7
4.00-19	4	TT/TL	3.0D	-	712	112	330	2145	72 A6 / 64 A8	355	280	3.4
4.00-19	6	TT/TL	3.0 D	-	715	115	328	2145	76 A6 / 68 A8	400	315	4.2
4.00-19	8	TL	3.0 D	-	715	115	328	2145	80A6/72A8	450	355	4.8
6.00-19	6	TT	4.5 E	4.00 E, 5.00 F	814	165	386	2445	93 A6 / 85 A8	650	515	3.3
6.00-19	8	TT	4.5 E	4.00 E, 5.00 F	814	165	386	2445	95 A6 / 87 A8	690	545	3.6
7.50-20	8	TT/TL	5.5 F	5.00 F,	915	205	431	2725	109 A6 / 101 A8	1030	825	3.4
7.50-20	10	TT/TL	5.5 F	5.00 F,	915	205	431	2725	113 A6 / 105 A8	1150	925	4.1