



Salient Features

Field and road tyre for 2WD tractors
Soil tillage and transport application
Improved steering control on fields

Applications

2WD Tractor

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
5.50-16	6	TT	4.0E	3.50 D, 4.50 E	710	150	330	2135	86A6/78A8	530	425	3.7
6.00-16DBG	4	TT	4.5 E	4.00 E, 5 K, 5.00 F	735	165	355	2210	80A6/73A8	450	365	2.8
6.00-16DBG	6	TT	4.5E	4.00 E, 5 K, 5.00 F	735	165	355	2210	88A6/80A8	560	450	3.3
6.00-16DBG	8	TT	4.5E	4.00 E, 5 K, 5.00 F	735	165	355	2210	94A6/86A8	670	530	4.5
6.00-16DBG	10	TT	4.5 E	4.00 E, 5 K, 5.00 F	735	165	355	2210	98A6/90A8	750	600	5
6.50-16	6	TT	4.5E	4.00 E, 5 K, 5.00 F 5.50 F	760	175	355	2295	91A6/83A8	615	487	3.1
6.50-16	8	TT	4.5E	4.00 E, 5 K, 5.00 F 5.50 F	760	175	355	2295	98A6/90A8	750	600	4.2
7.50-16	6	TT	5.5 F	5.00 F, 5 K, 6.00 F	805	205	383	2438	98A6/90A8	750	600	2.8
7.50-16	8	TT	5.5 F	5.00 F, 5 K, 6.00 F	805	205	383	2438	103A6/96A8	875	710	3.7
7.50-16	10	TT	5.5 F	5.00 F, 5 K, 6.00 F	805	205	383	2438	109A6/101A8	1030	825	4.8
7.50-18	8	TT/TL	5.5 F	-	860	205	405	2615	106A6/98A8	950	750	3.7
6.50-20	8	TT	5.00F	4.00 E, 5.50 F	864	180	406	2565	102A6/95A8	850	690	4.5
6.50-20	10	TT	5.00F	4.00 E, 5.50 F	864	180	406	2565	107A6/100A8	975	800	5.0
7.50-20	6	TT	5.5 F	5.00 F	915	205	425	2727	103A6/99A8	875	775	2.8
7.50-20	8	TT	5.5 F	5.00 F	915	205	425	2727	109A6/101A8	1030	825	3.4
7.50-20	10	TT	5.5 F	5.00 F	915	205	425	2727	113A6/105A8	1150	925	4.8