



Salient Features

Multi-angled and bold lug-bars for service durability and self-cleaning.
 Suitably designed lug bar spacing for comfort drive & added traction.
 Strong and sturdy body plies for longer service durability.
 Tread contact patch with broader lugs for heavy duty prime-movers.

Applications

2WD Tractor

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
4.50-10	4	TT	3.00D	-	505	121	235	1475	59A6/55A8	243	218	3.0
4.50-10	6	TT	3.00D	-	505	121	235	1475	66A6/63A8	307	272	4.5
5.20-14	6	TT	4.0	-	645	145	301	1938	79A6/75A8	437	387	4.5
5.00-16	6	TT	4.0	3.00D 4.00J	680	140	322	2032	84A6/76A8	500	400	4.2
5.50-16	4	TT	4.0E	3.50 D, 4.50 E	710	150	331	2116	78A6/71A8	425	345	2.5
5.50-16	6	TT	4.0E	3.50 D, 4.50 E	710	150	331	2116	86A6/78A8	530	425	3.7
5.50-16	8	TT	4.0E	3.50 D, 4.50 E	710	150	331	2116	92A6/84A8	630	500	4.5
5.50-16	10	TT	4.0E	3.50 D, 4.50 E	710	150	331	2116	94A6/86A8	670	536	5.2
6.00-16DBG	8	TT	4.5E	4.00 E, 5 K, 5.00 F	740	170	355	2205	94A6/86A8	670	530	4.5
6.00-16DBG	10	TT	4.5 E	4.00 E, 5 K, 5.00 F	740	170	355	2205	98A6/90A8	750	600	5.0
6.50-16	8	TT	4.5E	4.00 E, 5 K, 5.00 F 5.50 F	765	180	359	2280	98A6/90A8	750	600	4.2
7.50-16	8	TT	5.5F	5.00 F, 5 K, 6.00 F	810	205	383	2438	103A6/96A8	875	710	3.7
7.50-16	10	TT	5.5F	5.00 F, 5 K, 6.00 F	810	205	383	2438	109A6/101A8	1030	825	4.8
6.50-20	10	TT	5.00F	4.00 E, 5.50 F	864	180	406	2565	107A6/99A8	975	775	5.5