



## Salient Features

- Excellent load distribution during heavy loads.
- Strong and sturdy body plies for longer service durability.
- Excellent flotation and mobility from four rib design.
- Tread contact patch with multi ribs for heavy duty prime-movers.

## Applications

2WD Tractor

Trailer

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
9.5L-15	6	TT/TL	7.0	8 LB	780	240	359	2330	99 A6 / 95 A8	775	690	2.5
9.5L-15	8	TT/TL	7.0	8 LB	780	240	359	2330	106 A6 / 102 A8	950	850	3.3
11L-15	8	TT/TL	8 LB	10 LB	795	279	380	2370	110 A6 / 106 A8	1060	950	3.0
11L-15	10	TT/TL	8 LB	10 LB	795	279	380	2370	114 A6 / 110 A8	1180	1060	3.6
10.00-16	8	TT/TL	8 LB	W 8 L	882	280	408	2625	115 A6 / 107 A8	1215	975	2.8
10.00-16	10	TL	8 LB	W 8 L	882	280	408	2625	119 A6 / 111 A8	1360	1090	3.9
11.00-16	8	TT/TL	10 LB	W 8, W 8 L	950	335	438	2820	118 A6 / 110 A8	1320	1060	2.5
11.00-16	10	TT/TL	10 LB	W 8, W 8 L	950	335	438	2820	122 A6 / 115 A8	1500	1215	3.1
11.00-16	12	TT	10 LB	W 8, W 8 L	950	335	438	2820	126 A6 / 123 A8	1700	1550	4.1
7.50-18	8	TT	5.5 F		874	208	405	2615	106 A6 / 98 A8	950	760	3.7