



Salient Features

- Suitable for wet and dry grounds
- Soil tillage and lawn & garden operations
- Ideal with trenchers, implement machinery
- Large contact area providing high traction

Applications

2WD Tractor

Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE
			REC.INCH	ALT.INCH						(Kgs)	(bar)	
31×15.5-15	8	TL	13LB	-	790	360	360	2300	116 B	1250	3.1	
31×15.5-15	10	TT	13LB	-	790	360	360	2300	120B	1400	3.7	
31×15.5-15	12	TL	13LB	-	790	360	360	2300	124 B	1600	5.2	
31×15.5-15	16	TL	13LB	-	790	360	360	2300	130 B	1900	6.2	
23×10.50-12	6	TL	8.1/2JA	7JA	590	255	260	1682	100 A3	800	2.2	
23×10.50-12	8	TL	8.1/2JA	7JA	590	255	260	1682	107 A3	975	3	
23×10.50-12	10	TL	8.1/2JA	7JA	590	255	260	1682	111 A3	1090	3.8	
29×12.50-15	6	TL	10LB	-	755	312	330	2150	98B	750	2.1	
29×12.50-15	8	TL	10LB	-	755	312	330	2150	106B	950	3.1	