



Salient Features

- Better traction in all weather conditions.
- Effective self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

Applications

Backhoe

MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	PRESSURE
			REC.INCH	ALT.INCH						(Kgs)	(bar)
16.9-24	8	TL	DW15L	DW14L	1310	429	584	3838	142A8	2650	1.9
16.9-24	10	TL	DW15L	DW14L	1310	429	584	3838	146A8	3000	2.2
16.9-24	12	TL	DW15L	DW14L	1310	429	584	3838	149A8	3250	2.6
16.9-24	14	TL	DW15L	DW14L	1310	429	584	3838	152A8	3450	3.0
16.9-24	16	TL	DW15L	DW14L	1310	429	584	3838	153A8	3650	3
17.5L-24	8	TL	DW15L	DW14L	1270	445	560	3683	139A8	2430	1.7
17.5L-24	10	TL	DW15L	DW14L	1270	445	560	3683	144A8	2800	2.2
17.5L-24	12	TL	DW15L	DW14L	1270	445	570	3683	148A8	3150	2.7
17.5L-24	14	TL	DW15L	DW14L	1270	445	570	3683	150A8	3350	3.1
17.5L-24	16	TL	DW15L	DW14L	1270	445	570	3683	152A8	3550	3.4
17.5L-24	18	TL	DW15L	DW14L	1270	445	570	3683	154 A8	3750	3.8
18.4-24	12	TL	DW16L	-	1375	467	620	4015	155A8	3875	2.5
18.4-24	14	TL	DW16L	-	1375	467	620	4015	158A8	4250	2.9
18.4-24	16	TL	DW16L	-	1375	467	620	4015	159A8	4375	3
19.5L-24	12	TL	DW16L	-	1325	490	584	3835	151A8	3450	2.3
19.5L-24	14	TL	DW16L	-	1325	490	584	3835	154A8	3750	2.7
19.5L-24	16	TL	DW16L	-	1325	490	584	3835	157A8	4125	3
21L-24	12	TL	DW18L	-	1377	533	610	3988	155A8	3875	2.2
21L-24	14	TL	DW18L	-	1377	533	610	3988	157 A8	4125	2.4
21L-24	16	TL	DW18L	-	1377	533	610	3988	159A8	4375	2.6
16.9-28	8	TL	DW15L	DW14L	1410	429	635	4140	145A8	2900	1.9
16.9-28	10	TL	DW15L	DW14L	1410	429	635	4140	148A8	3150	2.2
16.9-28	12	TT/TL	DW15L	DW14L	1410	429	635	4140	152A8	3550	2.6

MTU 428



16.9-28	14	TL	DW15L	DW14L	1410	429	635	4140	154A8	3750	2.9
16.9-28	16	TT/TL	DW15L	DW14L	1410	429	635	4140	157A8	4125	3.1
18.4-26	10	TL	DW16L	DW15L	1425	467	635	4191	153A8	3650	2.1
18.4-26	12	TL	DW16L	DW15L	1425	467	635	4191	156A8	4000	2.5
18.4-26	14	TL	DW16L	DW15L	1425	467	635	4191	159A8	4375	2.9
18.4-26	16	TT/TL	DW16L	DW15L	1425	467	635	4191	162A8	4750	3.2