



Salient Features

- Better traction in all weather conditions.
- Effective self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

Applications

Backhoe

MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	PRESSURE
			REC.INCH	ALT.INCH						(Kgs)	(bar)
16.9-28	8	TL	DW15L	DW14L	1410	429	635	4140	145 A8	2900	1.9
16.9-28	10	TL	DW15L	DW14L	1410	429	635	4140	148 A8	3150	2.2
16.9-28	12	TL	DW15L	DW14L	1410	429	635	4140	152 A8	3550	2.6
16.9-28	14	TL	DW15L	DW14L	1410	429	635	4140	154 A8	3750	2.9
18.4-26	10	TL	DW16L	DW15L	1425	467	635	4191	153 A8	3650	2.1
18.4-26	12	TL	DW16L	DW15L	1425	467	635	4191	156 A8	4000	2.5
18.4-26	14	TL	DW16L	DW15L	1425	467	635	4191	159 A8	4375	2.9
18.4-26	16	TL	DW16L	DW15L	1425	467	635	4191	162 A8	4750	3.2