



Salient Features

- Better traction in all weather conditions.
- Effective self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

Applications

Backhoe

MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH						(Kgs)		
12.5/70-16	8	TL	10LB	-	856	315	380	2590	125 A2	1650		2.6
12.5/70-16	10	TL	10LB	-	856	315	380	2590	129 A2	1850		3.0
12.5/70-16	12	TL	10LB	-	856	315	380	2590	132 A2	2000		3.4
12.5/70-16	14	TL	10LB	-	856	315	380	2590	134 A2	2120		3.7
15.5/60-18	10	TL	W13	-	950	400	438	2870	139 A2	2430		2.6
15.5/60-18	12	TL	W13	-	950	400	438	2870	142 A2	2650		3.1
15.5/60-18	14	TL	W13	-	950	400	438	2870	144 A2	2800		3.6
400/70-20	16	TL	13	12 SDC, 13 SDC	1097	408	487	3214	149 A8	3250		4.0
17.5/65-20	10	TL	W14L	-	1090	450	488	3300	150 A2	3350		2.4
17.5/65-20	12	TL	W14L	-	1090	450	488	3300	153 A2	3650		2.8
17.5/65-20	14	TL	W14L	-	1090	450	488	3300	155 A2	3875		3.2
16.9-24	12	TL	DW15L	-	1310	429	603	3878	149 A8	3250		2.6
16.9-24	14	TL	DW15L	-	1310	429	603	3878	152 A8	3550		2.8
16.9-24	16	TL	DW15L	-	1310	429	603	3878	153 A8	3650		3.0
19.5L-24	12	TL	DW16L	-	1305	482	587	3936	151 A8	3450		2.3
400/80-24	20	TL	W13	W12, W14L	1262	394	566	3655	162 A8	4750		5.0
440/80-24	22	TL	DW15L	DW14L	1315	450	625	3986	168 A8	5600		5.0
18.4-26	12	TL	DW16L	DW15L	1425	480	636	4133	156 A8	4000		2.5
16.9-28	12	TL	DW15L	DW14L	1410	450	645	4247	152 A8	3550		2.6