



Salient Features

Low section flotation tyres offering high load capacity with minimum soil compaction.

Well Suited for both on and off road applications.

Applicable in high flotation and trailers.

Available with dual bead and reinforced side wall for extra load carrying capacity.

Applications

Forest Harvester

Forest Trailer

Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)		30KMPH (Kgs)	40KMPH (Kgs)	(bar)
500/50-17	14	TL	16.0	-	960	490	406	2750	149 A6 / 145 A8	3250	2900	2.8	155 A6 / 151 A8	3875	3450	3.4
500/50-17	16	TL	16.0	-	960	490	406	2750	152 A6 / 148 A8	3550	3150	3.4	158 A6 / 154 A8	4250	3750	4.2
500/50-17	18	TL	16.0	-	960	490	380	2750	154 A6 / 150 A8	3750	3350	4.2	160 A6 / 156 A8	4500	4000	5.0