



Salient Features

Low section flotation tyres offering high load capacity with minimum soil compaction.

Well Suited for both on and off road applications.

Applicable in high flotation and trailers.

Available with dual bead and reinforced side wall for extra load carrying capacity.

Applications

Baler

Trailer

SIZES

| SIZE | PR | TYPE | RIM | | O.D (mm) | S.W (mm) | SLR (mm) | RC (mm) | LI/SS | MAX. LOAD | | INFLATION PRESSURE (bar) |
|-------------|----|------|----------|----------|-------------|-------------|-------------|------------|----------------|-----------------|-----------------|--------------------------------|
| | | | REC.INCH | ALT.INCH | | | | | | 40KMPH (Kgs) | 50KMPH (Kgs) | |
| 550/60-22.5 | 12 | TL | AG 16.00 | - | 1240 | 550 | 540 | 3735 | 161 A8 / 157 B | 4625 | 4125 | 2.1 |
| 550/60-22.5 | 16 | TL | AG 16.00 | - | 1240 | 550 | 540 | 3735 | 167 A8 / 163 B | 5450 | 4875 | 2.8 |
| 600/55-22.5 | 12 | TL | AG 20.00 | - | 1240 | 600 | 540 | 3735 | 164 A8 / 160 B | 5000 | 4500 | 2.0 |
| 600/55-22.5 | 16 | TL | AG 20.00 | - | 1240 | 600 | 540 | 3735 | 169 A8 / 166 B | 5800 | 5300 | 2.6 |
| 600/50-22.5 | 12 | TL | AG 20.00 | - | 1170 | 600 | 508 | 3501 | 159 A8 / 156 B | 4375 | 4000 | 2.0 |
| 600/50-22.5 | 16 | TL | AG 20.00 | - | 1170 | 600 | 508 | 3501 | 165 A8 / 161 B | 5150 | 4625 | 2.6 |
| 600/50-22.5 | 18 | TL | AG 20.00 | - | 1170 | 600 | 508 | 3501 | 167 A8 / 163 B | 5450 | 4875 | 2.9 |
| 700/40-22.5 | 12 | TL | AG 24.00 | - | 1170 | 700 | 508 | 3530 | 160 A8 / 157 B | 4500 | 4125 | 1.7 |
| 700/40-22.5 | 16 | TL | AG 24.00 | - | 1170 | 700 | 508 | 3530 | 166 A8 / 162 B | 5300 | 4750 | 2.2 |