



## Salient Features

Radial tire for Row Crop application

Designed for modern harvesting machines.

Narrow tread protecting the soil and avoids damage to the delicate crop.

Tread design with rounded shoulder

Excellent traction performance

## Applications

2WD Tractor

4WD Tractor

MFWA

Sprayer

SIZES													
SIZE	O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	RIM		Bar REC.INCH	Bar ALT.INCH	KM/H	Load capacity (kg/tyre)			
					W7	W6							
210/95R32 116D/119A8 (Replaces 8.3R32)	1190	214	536	3511	W7	W6	65	875	1250	-	-	-	-
							50	920	1310	-	-	-	-
							40	960	1370	-	-	-	-
							25	1040	1480	-	-	-	-
							Field	1010	1440	-	-	-	-
230/95R32 128D/131A8 (Replaces 9.5R32)	1245	240	560	3673	W8	W7	65	1215	1800	-	-	-	-
							50	1280	1890	-	-	-	-
							40	1330	1970	-	-	-	-
							25	1440	2130	-	-	-	-
							Field	1400	2070	-	-	-	-
270/95R32 132D/135A8 (Replaces 11.2R32)	1300	275	585	3835	W10	W9	65	1450	2000	-	-	-	-
							50	1520	2100	-	-	-	-
							40	1590	2190	-	-	-	-
							25	1720	2370	-	-	-	-
							Field	1670	2300	-	-	-	-
230/95R36 130D/133A8 (Replaces 9.5R36)	1345	240	605	3968	W8	W7	65	1285	1900	-	-	-	-
							50	1350	2000	-	-	-	-
							40	1410	2080	-	-	-	-
							25	1520	2250	-	-	-	-
							Field	1480	2190	-	-	-	-

270/95R36 136D/139A8 (Replaces 11.2R36)	1410	275	635	4160	W9	W10	65	1550	2240	-	-	-
							50	1630	2350	-	-	-
							40	1700	2450	-	-	-
							25	1840	2650	-	-	-
							Field	1740	2580	-	-	-
230/95R44 134D/137A8 (Replaces 9.5R44)	1550	240	698	4573	W9	W10	65	1450	2120	-	-	-
							50	1520	2230	-	-	-
							40	1590	2320	-	-	-
							25	1720	2510	-	-	-
							Field	1670	2440	-	-	-
270/95R44 140D/143A8 (Replaces 11.2R44)	1605	275	722	4735	W 10	W9, W8	65	1750	2500	-	-	-
							50	1840	2630	-	-	-
							40	1920	2740	-	-	-
							25	2070	2960	-	-	-
							Field	2010	2880	-	-	-
230/95R48 136D/139A8 (Replaces 9.5R48)	1650	240	743	4868	W8	W7	65	1550	2240	-	-	-
							50	1630	2350	-	-	-
							40	1700	2450	-	-	-
							25	1840	2650	-	-	-
							Field	1780	2580	-	-	-
270/95R48 142D/145A8 (Replaces 11.2R48)	1710	275	770	5045	W9	W10	65	1850	2650	-	-	-
							50	1940	2780	-	-	-
							40	2030	2900	-	-	-
							25	2190	3140	-	-	-
							Field	2130	3050	-	-	-
270/95R38 140A8/137D	1479	275	665.6	4363.1	W9	W10	65	-	2300	-	-	-
							50	-	2420	-	-	-
							40	-	2520	-	-	-
							25	-	2730	-	-	-
							Field	-	2650	-	-	-
230/95R42 136A8/133D	1505	240	677.3	4439.8	W8	W7	65	-	-	2060	-	-
							50	-	-	2160	-	-
							40	-	-	2260	-	-
							25	-	-	2440	-	-
							Field	-	-	2370	-	-
270/95R42 142A8/139D	1565	284	736	4831	W9	W10	65	-	2430	-	-	-
							50	-	2550	-	-	-
							40	-	2660	-	-	-
							25	-	2880	-	-	-
							Field	-	2790	-	-	-
300/95R46 151A8/148D	1738	295	782.1	5127.1	W9	W10	65	-	3150	-	-	-
							50	-	3310	-	-	-
							40	-	3450	-	-	-
							25	-	3730	-	-	-
							Field	-	3620	-	-	-

380/90R46 155A8/B	1852	380	833.4	5463.4	W12	W13	65	-	-	-	-	-
							50	-	3875	-	-	-
							40	-	3875	-	-	-
							25	-	4150	-	-	-
							Field	-	5235	-	-	-
340/85R48 152A8/B	1797	343	808.65	5301.15	W11	W12	65	-	-	-	-	-
							50	-	-	3550	-	-
							40	-	-	3550	-	-
							25	-	-	3800	-	-
							Field	-	-	4900	-	-
320/90R50 153A8/150D	1846	319	830.7	5445.7	W10	W9, W8	65	-	3350	-	-	-
							50	-	3520	-	-	-
							40	-	3670	-	-	-
							25	-	3970	-	-	-
							Field	-	3850	-	-	-
380/90R50 154A8/151D	1954	380	879.3	5764.3	W12	W13	65	3450	-	-	-	-
							50	3620	-	-	-	-
							40	3780	-	-	-	-
							25	4090	-	-	-	-
							Field	3970	-	-	-	-
300/95R52 151A8/148D	1890	310	896	5818	W10	W11	65	-	3150	-	-	-
							50	-	3310	-	-	-
							40	-	3450	-	-	-
							25	-	3730	-	-	-
							Field	-	3620	-	-	-
320/90R54 155A8/152D	1948	319	876.6	5746.6	W10	W9, W8	65	-	-	-	-	-
							50	-	3875	-	-	-
							40	-	3875	-	-	-
							25	-	4150	-	-	-
							Field	-	5525	-	-	-
270/95R54 146A8/B	1885	275	878	5815	W9	W8, W10	65	-	-	3000	-	-
							50	-	-	3000	-	-
							40	-	-	3210	-	-
							25	-	-	4140	-	-
							Field	-	-	4070	-	-