



Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

Applications

Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)		30KMPH (Kgs)	40KMPH (Kgs)	(bar)
200/60-14.5	10	TT/TL	6.75	4.5E,5.5E	610	210	278	1785	106A6/102A8	950	850	5.7	113A6/109A8	1150	1030	6.9
200/60-14.5	12	TT/TL	6.75	4.5E,5.5E	610	210	278	1785	107A6/103A8	975	875	5.8	114A6/110A8	1180	1060	7.0
200/60-14.5	14	TT/TL	6.75	4.5E,5.5E	610	210	278	1785	108A6/104A8	1000	900	5.9	115A6/111A8	1215	1090	7.1
250/65-14.5	12	TT/TL	AG 8	6.75	675	255	303	1978	118A6/114A8	1320	1180	6.0	125A6/123A8	1650	1550	6.9
250/65-14.5	14	TT/TL	AG 8	6.75	675	255	303	1978	123A6/119A8	1550	1360	6.0	130A6/126A8	1900	1700	7.5