



Salient Features

- Excellent design for modern day farming.
- Innovative design for high load capacity.
- Excellent flotation characteristics.
- Minimizes field disturbance.
- Special cut resistant compound.
- Deep tread depth for longer life.
- Excellent self-cleaning property
- Special rim guard protecting rim flange from damage.

Applications

2WD Tractor

4WD Tractor

Combine Harvester

MFWA

SIZES

SIZE	O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	RIM		Bar	0.60	0.80	1.00	1.20	1.40	1.60	2.00	2.40	2.80	3.20	3.60
					REC.INCH	ALT.INCH												
440/65R24 135 D/138 A8	1182	441	532	3487	W14L	W13, W15L	65	1050	1225	1375	1530	1680	1810	2010	2180	-	-	-
							50	1100	1285	1445	1605	1765	1905	2110	2290	-	-	-
							40	1135	1325	1490	1655	1820	1960	2175	2360	-	-	-
							30	1205	1410	1585	1760	1935	2085	2310	2510	-	-	-
							10LT	1405	1640	1845	2050	2255	2430	2695	2925	-	-	-
							10HT	1205	1410	1585	1760	1935	2085	2310	2510	-	-	-
540/65R34 152D/155 A8	1566	550	705	4620	W16L	W18L	65	1705	1990	2240	2485	2735	2950	3270	3555	-	-	-
							50	1795	2090	2350	2615	2875	3100	3435	3730	-	-	-
							40	1860	2170	2445	2715	2985	3220	3565	3880	-	-	-
							30	1965	2290	2575	2860	3150	3395	3760	4085	-	-	-
							10LT	2285	2670	3000	3335	3670	3955	4380	4760	-	-	-
							10HT	1965	2290	2575	2860	3150	3395	3760	4085	-	-	-
480/65 R28* 145A8/142D	1335	479	610	4058	W15L	W14L	65	1275	1485	1670	1855	2045	2200	2440	2650	-	-	-
							50	1340	1560	1755	1950	2145	2315	2565	2785	-	-	-
							40	1395	1625	1830	2030	2235	2410	2670	2900	-	-	-
							30	1465	1710	1925	2135	2350	2535	2810	3050	-	-	-
							10LT	1710	1995	2240	2490	2740	2955	3275	3555	-	-	-
							10HT	1465	1710	1925	2135	2350	2535	2810	3050	-	-	-

RRT 665



540/65 R28* 152A8/149D	1413	530	643	4253	W16L	W18L	65	1560	1820	2050	2275	2505	2700	2990	3250	-	-	-
							50	1640	1915	2155	2395	2630	2835	3145	3415	-	-	-
							40	1705	1990	2240	2485	2735	2950	3270	3550	-	-	-
							30	1800	2095	2360	2620	2880	3105	3445	3740	-	-	-
							10LT	2095	2440	2745	3050	3355	3615	4010	4355	-	-	-
							10HT	1800	2095	2360	2620	2880	3105	3445	3740	-	-	-
540/65 R30* 153A8/150D	1464	530	670	4403	W16L	W18L	65	1610	1880	2115	2345	2580	2785	3085	3350	-	-	-
							50	1690	1975	2220	2465	2715	2925	3240	3520	-	-	-
							40	1755	2045	2300	2555	2815	3030	3360	3650	-	-	-
							30	1855	2160	2430	2700	2970	3200	3550	3855	-	-	-
							10LT	2160	2515	2830	3145	3460	3730	4135	4490	-	-	-
							10HT	1855	2160	2430	2700	2970	3200	3550	3855	-	-	-
600/65 R38* 162A8/159D	1745	600	790	5245	DW 20B	DW 18L	65	2100	2450	2760	3065	3370	3635	4025	4375	-	-	-
							50	2210	2575	2895	3220	3540	3815	4230	4595	-	-	-
							40	2280	2660	2995	3325	3660	3945	4370	4750	-	-	-
							30	2420	2820	3175	3525	3880	4180	4635	5035	-	-	-
							10LT	2820	3285	3695	4110	4520	4870	5400	5865	-	-	-
							10HT	2420	2820	3175	3525	3880	4180	4635	5035	-	-	-
650/65 R38* 166A8/163D	1810	645	830	5483	DW 20B	-	65	2340	2730	3075	3415	3755	4050	4485	4875	-	-	-
							50	2460	2870	3230	3585	3945	4250	4715	5120	-	-	-
							40	2545	2970	3340	3710	4085	4400	4880	5300	-	-	-
							30	2695	3145	3535	3930	4320	4660	5165	5610	-	-	-
							10LT	3140	3660	4120	4575	5035	5425	6015	6535	-	-	-
							10HT	2695	3145	3535	3930	4320	4660	5165	5610	-	-	-
650/65 R38* 174A8/171D	1810	645	830	5483	DW 20B	-	65	2215	2585	2830	3385	3750	4120	4490	4795	5230	5660	6150
							50	2325	2715	2975	3555	3940	4330	4715	5040	5490	5945	6460
							40	2415	2815	3085	3685	4090	4490	4890	5230	5695	6165	6700
							30	2550	2975	3255	3890	4315	4740	5165	5520	6015	6510	7075
							10LT	2965	3460	3790	4530	5025	5520	6015	6425	7005	7580	8240
							10HT	2550	2975	3255	3890	4315	4740	5165	5520	6015	6510	7075
650/65 R42* 168A8/165D	1913	645	878	5824	DW 20B	-	65	2475	2885	3245	3605	3970	4275	4740	5150	-	-	-
							50	2600	3030	3410	3790	4170	4495	4980	5410	-	-	-
							40	2690	3147	3530	3920	4315	4650	5155	5600	-	-	-
							30	2845	3320	3735	4150	4565	4920	5455	5925	-	-	-
							10LT	3315	3870	4355	4835	5320	5735	6355	6905	-	-	-
							10HT	2845	3320	3735	4150	4565	4920	5455	5925	-	-	-
650/65 R42* 173A8/170D	1913	645	878	5824	DW 20B	-	65	2460	2880	3300	3720	4140	4560	4800	5100	5580	6000	-
							50	2583	3024	3465	3906	4347	4788	5040	5355	5859	6300	-
							40	2681	3139	3597	4055	4513	4970	5232	5559	6082	6540	-
							30	2829	3312	3795	4278	4761	5244	5520	5865	6417	6900	-
							10LT	3296	3859	4422	4985	5548	6110	6432	6834	7477	8040	-
							10HT	2829	3312	3795	4278	4761	5244	5520	5865	6417	6900	-