

Size	LRP	LI	SS	OD	OW	SLR	RM	MRL Single	MRL Dual	F	W	NR (dB)	NG	
				mm	mm	mm	in	(kg@kPa)	(kg@kPa)					
11R22.5	16	148/145	M	1056	278	492	8.25	3150@850	2900@850	E	B	73	2	
12R22.5	16	152/148	M	1091	307	507	9	3550@850	3150@850	D	B	73	2	
295/80R22.5	16	152/148	M	1056	296	492	9	3550@850	3150@850	D	B	75	3	
315/70R22.5	18	154/150	L	1018	310	470	9	3750@900	3350@900	E	B	75	3	
315/70R22.5	16	152/148	M	1018	310	470	9	3550@850	3150@850	E	B	75	2	
315/80R22.5	18	156/150	L	1083	312	503	9	4000@850	3350@850	C	B	72	2	

Sailun's premium steer tyre, featuring extra wide shoulders with built in sipes for excellent stability and traction under all weather conditions.

An extra deep 16 – 17.5 mm tread depth ensures exceptional mileage, while an interlocking symmetrical tread block design promotes even wear and a square footprint.



Multi-sipes improve traction in wet conditions and dissipate heat for prolong tread life




Unique tread wall grooves help reduce irregular wear and improve traction

Stone ejectors protect tyre from stone drilling



Extra deep tread pattern (16 – 17.5 mm) with special compound for extended tread life

Wide footprint and square shoulder design for improved stability and mileage



THE SAILUN ENVIRONMENTALLY-FRIENDLY TECHNOLOGY (EFT) PROGRAMME

Our EFT programme demonstrates Sailun's commitment to delivering more for your investment while minimising environmental impacts. Tyres designated as EFT offer lower rolling resistance, and reduce fuel costs.

These tyres have also gained approval from the United States Environmental Protection Agency (USEPA) as part of the SmartWay® Verified Technologies scheme. This is a public / private collaboration between the USEPA and the transportation industry, helping carriers and logistics companies to improve fuel-efficiency and save money. SmartWay® Verified tyres can reduce NO_x emissions and fuel use by over 3%.