






The S629 is a directional position tyre suitable for mid to long distance trucks and buses running on good roads. Tread compound formula improves scrub resistance. Unique shoulder design and deeper shoulder grooves help prevent abnormal tyre wear. Widened running surface provides better tread-to-ground contact area for improved handling.







- Shallow pattern grooves provide the tyre with strong grip and skid resistance.
- The widened running surface provides even contact pressure for better handling.
- Zigzag pattern at the bottom of the tread grooves provide for better maneouverability and driving comfort.
- The widened shoulder and unique shoulder groove design provide for cool running and reduce uneven wear.



| | | | | | | | | | L.C.C. | | | | | |
|-------------|------------------|------|------|------|------|------|------|-------------|----------|----------|----|----|----------|----|
| Size | L.I. | S.R. | P.R. | T.D. | RIM | O.D. | S.W. | Std. RIM | Single | Dual | RR | WG | NG DB | NG |
| | | | | mm | inch | mm | mm | inch | kg | kg | | | | |
| | | | | | | | | | | | | | | |
| 285/70R19.5 | 146/144(144/142) | L(M) | 16PR | 15 | 19.5 | 895 | 283 | 8.25 | 3000@900 | 2800@900 | С | В | 73 | 2 |
| 295/80R22.5 | 154/149 | М | 18PR | | 22.5 | | | | | | | | | |
| 315/70R22.5 | 154/150(152/148) | L(M) | 18PR | * | 22.5 | * | * | * | * | * | С | В | 73 | 2 |
| 315/70R22.5 | 156/150 | L | 18PR | 16 | 22.5 | 1014 | 312 | 9 | 4000@900 | 3350@900 | С | В | 73 | 2 |
| 315/80R22.5 | 156/150(154/150) | L(M) | 18PR | 17 | 22.5 | 1076 | 312 | 9 | 4000@850 | 3350@850 | С | В | 73 | 2 |
| 385/55R22.5 | 160(158) | K(L) | 20PR | 14.5 | 22.5 | 996 | 386 | 12.25 | 4500@900 | | С | В | 73 | 2 |
| | | | | | | | | | | | | | | |

* Data available on request