



## **S696**

The S696 is a low section tyre designed to replace the traditional double-tyre style. The special tread rubber design allows the tyre to run cool. Strengthened design improves driving safety.





## Features & Benefits:

- Small grooves allow the tyre to run cool and provide better grip to improve skid resistance.
- Closed-shoulder design enhances tread wear resistance and effectively uneven wear.
- Zigzagged grooves reduce stone retention.
- Super wide running surface, shoulder design, and special tread formula improve tread life.





									L.	C.C.				
Size	L.I.	S.R.	P.R.	T.D.	RIM	O.D.	S.W.	Std. RIM	Single	Dual	RR	WG	NG DB	NG
				mm	inch	mm	mm	inch	kg	kg				
435/50R19.5	160	J	20PR		19.5									
445/45R19.5	160	J	20PR	13.5	19.5	895	446	15	4500@900		С	В	73	2
385/55R22.5	160(158)	K(L)	20PR	15	22.5	996	386	12.25	4500@900		D	А	76	3
385/65R22.5	160(158)	K(L)	20PR	16	22.5	1072	389	11.75	4500@900	*	С	А	72	2
445/65R22.5	169	K	20PR	16	22.5	1150	444	13	5800@900	*	С	В	73	2

\* Data available on request